pgcopydb Release 0.9

Dimitri Fontaine

Sep 30, 2022

DOCUMENTATION TABLE OF CONTENTS

1	Intro	duction to pgcopydb	3
	1.1	Feature Matrix	3
	1.2	pgcopydb uses pg_dump and pg_restore	4
	1.3	Change Data Capture, or fork and follow	4
2	Desig	n Considerations	5
	2.1	Bypass intermediate files for the TABLE DATA	5
	2.2	Notes about concurrency	5
	2.3	For each table, build all indexes concurrently	7
	2.4	Same-table Concurrency	8
3	Instal	lling pgcopydb	11
-	31	debian nackages	11
	3.2	RPM nackages	11
	3.2	Docker Images	11
	3.1	Build from sources	12
	5.4		12
4	Manu	al Pages	13
	4.1	pgcopydb	13
	4.2	pgcopydb clone	15
	4.3	pgcopydb follow	25
	4.4	pgcopydb snapshot	31
	4.5	pgcopydb copy	32
	4.6	ngcopydb dump	11
	47	ngcopyde damp	14
	4.8	ngconydb list	50
	49	ngconvdh stream	,0 17
	4.10	pgcopydb configuration	31

5 Indices and tables

The pgcopydb project is an Open Source Software project. The development happens at https://github.com/dimitri/pgcopydb and is public: everyone is welcome to participate by opening issues, pull requests, giving feedback, etc.

Remember that the first steps are to actually play with the pgcopydb command, then read the entire available documentation (after all, I took the time to write it), and then to address the community in a kind and polite way — the same way you would expect people to use when addressing you.

INTRODUCTION TO PGCOPYDB

pgcopydb is a tool that automates copying a PostgreSQL database to another server. Main use case for pgcopydb is migration to a new Postgres system, either for new hardware, new architecture, or new Postgres major version.

The idea would be to run $pg_dump -jN | pg_restore -jN$ between two running Postgres servers. To make a copy of a database to another server as quickly as possible, one would like to use the parallel options of pg_dump and still be able to stream the data to as many $pg_restore$ jobs. Unfortunately, that approach can't be implemented by using pg_dump and $pg_restore$ directly, see *Bypass intermediate files for the TABLE DATA*.

When using pgcopydb it is possible to achieve both concurrency and streaming with this simple command line:

```
$ export PGCOPYDB_SOURCE_PGURI="postgres://user@source.host.dev/dbname"
$ export PGCOPYDB_TARGET_PGURI="postgres://role@target.host.dev/dbname"
$ pgcopydb clone --table-jobs 4 --index-jobs 4
```

See the manual page for *pgcopydb clone* for detailed information about how the command is implemented, and many other supported options.

1.1 Feature Matrix

Here is a comparison of the features available when using pg_dump and pg_restore directly, and when using pgcopydb to handle the database copying.

Feature	pgcopydb	pg_dump ; pg_restore
Single-command operation	\checkmark	
Snapshot consistency	\checkmark	\checkmark
Ability to resume partial run	\checkmark	
Advanced filtering	\checkmark	\checkmark
Tables concurrency	\checkmark	\checkmark
Same-table concurrency	\checkmark	
Index concurrency	\checkmark	\checkmark
Constraint index concurrency	\checkmark	
Schema	\checkmark	\checkmark
Large Objects	\checkmark	\checkmark
Vacuum Analyze	\checkmark	
Copy Freeze	\checkmark	
Roles	\checkmark	(needs pg_dumpall)
Tablespaces		(needs pg_dumpall)
Follow changes	\checkmark	

See documentation about pgcopydb *pgcopydb configuration* for its Advanced filtering capabilities.

1.2 pgcopydb uses pg_dump and pg_restore

The implementation of pgcopydb actually calls into the pg_dump and pg_restore binaries to handle a large part of the work, such as the pre-data and post-data sections. See pg_dump docs for more information about the three sections supported.

After using pg_dump to obtain the pre-data and the post-data parts, then pgcopydb restore the pre-data parts to the target Postgres instance using pg_restore.

Then pgcopydb uses SQL commands and the COPY streaming protocol to migrate the table contents, the large objects data, and to VACUUM ANALYZE tables as soon as the data is available on the target instance.

Then pgcopydb uses SQL commands to build the indexes on the target Postgres instance, as detailed in the design doc *For each table, build all indexes concurrently*. This allows to include *constraint indexes* such as Primary Keys in the list of indexes built at the same time.

1.3 Change Data Capture, or fork and follow

It is also possible with pgcopydb to implement Change Data Capture and replay data modifications happening on the source database to the target database. See the *pgcopydb follow* command and the pgcopydb clone –-follow command line option at *pgcopydb clone* in the manual.

The simplest possible implementation of *online migration* with pgcopydb, where changes being made to the source Postgres instance database are replayed on the target system, looks like the following:

```
$ pgcopydb clone --follow &
# later when the application is ready to make the switch
```

\$ pgcopydb stream sentinel set endpos --current

```
# later when the migration is finished, clean-up both source and target
$ pgcopydb stream cleanup
```

2

3

CHAPTER

DESIGN CONSIDERATIONS

The reason why pgcopydb has been developed is mostly to allow two aspects that are not possible to achieve directly with pg_dump and pg_restore, and that requires just enough fiddling around that not many scripts have been made available to automate around.

2.1 Bypass intermediate files for the TABLE DATA

First aspect is that for pg_dump and pg_restore to implement concurrency they need to write to an intermediate file first.

The docs for pg_dump say the following about the -- jobs parameter:

You can only use this option with the directory output format because this is the only output format where multiple processes can write their data at the same time.

The docs for pg_restore say the following about the --jobs parameter:

Only the custom and directory archive formats are supported with this option. The input must be a regular file or directory (not, for example, a pipe or standard input).

So the first idea with pgcopydb is to provide the --jobs concurrency and bypass intermediate files (and directories) altogether, at least as far as the actual TABLE DATA set is concerned.

The trick to achieve that is that pgcopydb must be able to connect to the source database during the whole operation, when pg_restore may be used from an export on-disk, without having to still be able to connect to the source database. In the context of pgcopydb requiring access to the source database is fine. In the context of pg_restore, it would not be acceptable.

2.2 Notes about concurrency

The pgcopydb too implements many operations concurrently to one another, by ways of using the fork() system call. This means that pgcopydb creates sub-processes that each handle a part of the work.

The process tree then looks like the following:

- pgcopydb clone -follow -table-jobs 4 -index-jobs 4
 - pgcopydb clone worker
 - * pgcopydb copy supervisor (--table-jobs 4)
 - 1. pgcopydb copy worker
 - 2. pgcopydb copy worker

- 3. pgcopydb copy worker
- 4. pgcopydb copy worker
- * pgcopydb blob worker
- 1. pgcopydb index/constraints worker (--index-jobs 4)
- 2. pgcopydb index/constraints worker (--index-jobs 4)
- 3. pgcopydb index/constraints worker (--index-jobs 4)
- 4. pgcopydb index/constraints worker (--index-jobs 4)
- 1. pgcopydb vacuum analyze worker (--table-jobs 4)
- 2. pgcopydb vacuum analyze worker (--table-jobs 4)
- 3. pgcopydb vacuum analyze worker (--table-jobs 4)
- 4. pgcopydb vacuum analyze worker (--table-jobs 4)
- * pgcopydb sequences reset worker
- pgcopydb follow worker
 - * pgcopydb stream receive
 - * pgcopydb stream transform
 - * pgcopydb stream catchup

We see that when using pgcopydb clone --follow --table-jobs 4 --index-jobs 4 then pgcopydb creates 20 sub-processes, including one transient sub-process each time a JSON file is to be converted to a SQL file for replay.

The 20 total is counted from:

• 1 clone worker + 1 copy supervisor + 4 copy workers + 1 blob worker + 4 index workers + 4 vacuum workers + 1 sequence reset worker

that's 1 + 1 + 4 + 1 + 4 + 4 + 1 = 16

• 1 follow worker + 1 stream receive + 1 stream transform + 1 stream catchup

that's 1 + 1 + 1 + 1 = 4

• that's 16 + 4 = 20 total

Here is a description of the process tree:

- When starting with the TABLE DATA copying step, then pgcopydb creates as many sub-processes as specified by the --table-jobs command line option (or the environment variable PGCOPYDB_TABLE_JOBS).
- A single sub-process is created by pgcopydb to copy the Postgres Large Objects (BLOBs) found on the source database to the target database.
- To drive the index and constraint build on the target database, pgcopydb creates as many sub-processes as specified by the --index-jobs command line option (or the environment variable PGCOPYDB_INDEX_JOBS).

It is possible with Postgres to create several indexes for the same table in parallel, for that, the client just needs to open a separate database connection for each index and run each CREATE INDEX command in its own connection, at the same time. In pgcopydb this is implemented by running one sub-process per index to create.

The --index-jobs option is global for the whole operation, so that it's easier to setup to the count of available CPU cores on the target Postgres instance. Usually, a given CREATE INDEX command uses 100% of a single core.

- To drive the VACUUM ANALYZE workload on the target database pgcopydb creates as many sub-processes as specified by the --table-jobs command line option.
- To reset sequences in parallel to COPYing the table data, pgcopydb creates a single dedicated sub-process.
- When using the --follow option then another sub-process leader is created to handle the three Change Data Capture processes.
 - One process implements *pgcopydb stream receive* to fetch changes in the JSON format and pre-fetch them in JSON files.
 - As soon as JSON file is completed, the pgcopydb stream transform worker transforms the JSON file into SQL, as if by calling the command *pgcopydb stream transform*.
 - Another process implements *pgcopydb stream catchup* to apply SQL changes to the target Postgres instance. This process loops over querying the pgcopydb sentinel table until the apply mode has been enabled, and then loops over the SQL files and run the queries from them.

2.3 For each table, build all indexes concurrently

pgcopydb takes the extra step and makes sure to create all your indexes in parallel to one-another, going the extra mile when it comes to indexes that are associated with a constraint.

Postgres introduced the configuration parameter synchronize_seqscans in version 8.3, eons ago. It is on by default and allows the following behavior:

This allows sequential scans of large tables to synchronize with each other, so that concurrent scans read the same block at about the same time and hence share the I/O workload.

The other aspect that pg_dump and pg_restore are not very smart about is how they deal with the indexes that are used to support constraints, in particular unique constraints and primary keys.

Those indexes are exported using the ALTER TABLE command directly. This is fine because the command creates both the constraint and the underlying index, so the schema in the end is found as expected.

That said, those ALTER TABLE ... ADD CONSTRAINT commands require a level of locking that prevents any concurrency. As we can read on the docs for ALTER TABLE:

Although most forms of ADD table_constraint require an ACCESS EXCLUSIVE lock, ADD FOREIGN KEY requires only a SHARE ROW EXCLUSIVE lock. Note that ADD FOREIGN KEY also acquires a SHARE ROW EXCLUSIVE lock on the referenced table, in addition to the lock on the table on which the constraint is declared.

The trick is then to first issue a CREATE UNIQUE INDEX statement and when the index has been built then issue a second command in the form of ALTER TABLE ... ADD CONSTRAINT ... PRIMARY KEY USING INDEX ..., as in the following example taken from the logs of actually running pgcopydb:

```
21:52:06 68898 INF0 COPY "demo"."tracking";
21:52:06 68899 INF0 COPY "demo"."client";
21:52:06 68899 INF0 Creating 2 indexes for table "demo"."client"
21:52:06 68906 INF0 CREATE UNIQUE INDEX client_pkey ON demo.client USING btree (client);
21:52:06 68907 INF0 CREATE UNIQUE INDEX client_pid_key ON demo.client USING btree (pid);
21:52:06 68908 INF0 CREATE UNIQUE INDEX tracking_pkey ON demo.tracking USING btree (client, ts);
21:52:06 68907 INF0 ALTER TABLE "demo"."client" ADD CONSTRAINT "client_pkey" PRIMARY KEY USING INDEX "client_pkey";
21:52:06 68908 INF0 ALTER TABLE "demo"."tracking" ADD CONSTRAINT "tracking_pkey" PRIMARY KEY USING INDEX "tracking_pkey";
```

This trick is worth a lot of performance gains on its own, as has been discovered and experienced and appreciated by pgloader users already.

2.4 Same-table Concurrency

In some database schema design, it happens that most of the database size on-disk is to be found in a single giant table, or a short list of giant tables. When this happens, the concurrency model that is implemented with --table-jobs still allocates a single process to COPY all the data from the source table.

Same-table concurrency allows pgcopydb to use more than once process at the same time to process a single source table. The data is then logically partitionned (on the fly) and split between processes:

• To fetch the data from the source database, the COPY processes then use SELECT queries like in the following example:

```
      COPY (SELECT * FROM source.table WHERE id BETWEEN
      1 AND 123456)

      COPY (SELECT * FROM source.table WHERE id BETWEEN
      123457 AND 234567)

      COPY (SELECT * FROM source.table WHERE id BETWEEN
      234568 AND 345678)
```

This is only possible when the source.table has at least one column of an integer type (int2, int4, and int8 are supported) and with a UNIQUE or PRIMARY KEY constraint. We must make sure that any given row is selected only once overall to avoid introducing duplicates on the target database.

• To decide if a table COPY processing should be split, the command line option split-tables-larger-than is used, or the environment variable PGCOPYDB_SPLIT_TABLES_LARGER_THAN.

The expected value is either a plain number of bytes, or a pretty-printed number of bytes such as 250 GB.

When using this option, then tables that have at least this amount of data and also a candidate key for the COPY partitioning are then distributed among a number of COPY processes.

The number of COPY processes is computed by dividing the table size by the threshold set with the split option. For example, if the threshold is 250 GB then a 400 GB table is going to be distributed among 2 COPY processes.

The command *pgcopydb list table-parts* may be used to list the COPY partitioning that pgcopydb computes given a source table and a threshold.

2.4.1 Significant differences when using same-table COPY concurrency

When same-table concurrency happens for a source table, some operations are not implemented as they would have been without same-table concurrency. Specifically:

• TRUNCATE and COPY FREEZE Postgres optimisation

When using a single COPY process, it's then possible to TRUNCATE the target table in the same transaction as the COPY command, as in the following syntethic example:

```
BEGIN;
TRUNCATE table ONLY;
COPY table FROM stdin WITH (FREEZE);
COMMIT
```

This technique allows Postgres to implement several optimisations, doing work during the COPY that would otherwise need to happen later when executing the first queries on the table.

When using same-table concurrency then we have several transactions happening concurrently on the target system that are copying data from the source table. This means that we have to TRUNCATE separately and the FREEZE option can not be used.

• CREATE INDEX and VACUUM

Even when same-table COPY concurrency is enabled, creating the indexes on the target system only happens after the whole data set has been copied over. This means that only the when the last process is done with the COPYing then this process will take care of the the indexes and the *vacuum analyze* operation.

2.4.2 Same-table COPY concurrency performance limitations

Finally, it might be that same-table concurrency is not effective at all in some use cases. Here is a list of limitations to have in mind when selecting to use this feature:

• Network Bandwidth

The most common performance bottleneck relevant to database migrations is the network bandwidth. When the bandwidth is saturated (used in full) then same-table concurrency will provide no performance benefits.

• Disks IOPS

The second most command performance bottleneck relevant to database migrations is disks IOPS and, in the Cloud, burst capacity. When the disk bandwidth is used in full, then same-table concurrency will provide no performance benefits.

Source database system uses read IOPS, target database system uses both read and write IOPS (copying the data writes to disk, creating the indexes both read table data from disk and then write index data to disk).

• On-disk data organisation

When using a single COPY process, the target system may fill-in the Postgres table in a clustered way, using each disk page in full before opening the next one, in a sequential fashion.

When using same-table COPY concurrency, then the target Postgres system needs to handle concurrent writes to the same table, resulting in a possibly less effective disk usage.

How that may impact your application performance is to be tested.

synchronize_seqscans

Postgres implemented this option back in version 8.3. The option is now documented in the Version and Platform Compatibility section.

The documentation reads:

This allows sequential scans of large tables to synchronize with each other, so that concurrent scans read the same block at about the same time and hence share the I/O workload.

The impact on performance when having concurrent COPY processes reading the same source table at the same time is to be assessed. At the moment there is no option in pgcopydb to *SET synchronize_seqscans TO off* when using same-table COPY concurrency.

Use your usual Postgres configuration editing for testing.

CHAPTER

THREE

INSTALLING PGCOPYDB

Several distributions are available for pgcopydb.

3.1 debian packages

Binary packages for debian and derivatives (ubuntu) are available from apt.postgresql.org repository, install by following the linked documentation and then:

\$ sudo apt-get install pgcopydb

3.2 RPM packages

The Postgres community repository for RPM packages is yum.postgresql.org and does not include binary packages for pgcopydb at this time.

3.3 Docker Images

Docker images are maintained for each tagged release at dockerhub, and also built from the CI/CD integration on GitHub at each commit to the *main* branch.

The DockerHub dimitri/pgcopydb repository is where the tagged releases are made available. The image uses the Postgres version currently in debian stable.

To use this docker image:

\$ docker run --rm -it dimitri/pgcopydb:v0.9 pgcopydb --version

Or you can use the CI/CD integration that publishes packages from the main branch to the GitHub docker repository:

```
$ docker pull ghcr.io/dimitri/pgcopydb:latest
$ docker run --rm -it ghcr.io/dimitri/pgcopydb:latest pgcopydb --version
$ docker run --rm -it ghcr.io/dimitri/pgcopydb:latest pgcopydb --help
```

3.4 Build from sources

Building from source requires a list of build-dependencies that's comparable to that of Postgres itself. The pgcopydb source code is written in C and the build process uses a GNU Makefile.

See our main Dockerfile for a complete recipe to build pgcopydb when using a debian environment.

Then the build process is pretty simple, in its simplest form you can just use make clean install, if you want to be more fancy consider also:

\$ make -s clean \$ make -s -j12 install

CHAPTER

FOUR

MANUAL PAGES

The pgcopydb command provides several sub-commands. Each of them have their own manual page.

4.1 pgcopydb

pgcopydb - copy an entire Postgres database from source to target

4.1.1 Synopsis

pgcopydb provides the following commands:

```
pgcopydb
  clone
           Clone an entire database from source to target
  fork
           Clone an entire database from source to target
           Replay changes from the source database to the target database
  follow
 snapshot Create and exports a snapshot on the source database
           Implement the data section of the database copy
+ copy
           Dump database objects from a Postgres instance
+ dump
+ restore
          Restore database objects into a Postgres instance
           List database objects from a Postgres instance
+ list
           Stream changes from the source database
+ stream
 help
           print help message
 version print pgcopydb version
```

4.1.2 Description

The pgcopydb command implements a full migration of an entire Postgres database from a source instance to a target instance. Both the Postgres instances must be available for the entire duration of the command.

The pgcopydb command also implements a full Logical Decoding client for the wal2json logical decoding plugin, allowing Change Data Capture to replay data changes (DML) happening on the source database after the base copy snapshot.

4.1.3 pgcopydb help

The pgcopydb help command lists all the supported sub-commands:

```
pgcopydb pgcopydb help
 pgcopydb
             Clone an entire database from source to target
   clone
   fork
             Clone an entire database from source to target
   follow
             Replay changes from the source database to the target database
             Copy an entire database from source to target
   copy-db
   snapshot
             Create and exports a snapshot on the source database
   copy
              Implement the data section of the database copy
  + dump
             Dump database objects from a Postgres instance
   restore
             Restore database objects into a Postgres instance
             List database objects from a Postgres instance
  + list
  + stream
             Stream changes from the source database
             print help message
   help
   version
             print pgcopydb version
 pgcopydb copy
   db
                Copy an entire database from source to target
   roles
                Copy the roles from the source instance to the target instance
   schema
                Copy the database schema from source to target
   data
                 Copy the data section from source to target
   table-data
                Copy the data from all tables in database from source to target
   blobs
                Copy the blob data from ther source database to the target
   sequences
                Copy the current value from all sequences in database from source to target
   indexes
                Create all the indexes found in the source database in the target
   constraints Create all the constraints found in the source database in the target
 pgcopydb dump
   schema
              Dump source database schema as custom files in work directory
   pre-data
              Dump source database pre-data schema as custom files in work directory
   post-data
              Dump source database post-data schema as custom files in work directory
              Dump source database roles as custome file in work directory
   roles
 pgcopydb restore
   schema
               Restore a database schema from custom files to target database
               Restore a database pre-data schema from custom file to target database
   pre-data
               Restore a database post-data schema from custom file to target database
   post-data
               Restore database roles from SQL file to target database
   roles
   parse-list Parse pg_restore --list output from custom file
 pacopydb list
   tables
                List all the source tables to copy data from
   table-parts
                List a source table copy partitions
   sequences
                List all the source sequences to copy data from
   indexes
                List all the indexes to create again after copying the data
                List all the dependencies to filter-out
   depends
 pgcopydb stream
              Setup source and target systems for logical decoding
   setup
              cleanup source and target systems for logical decoding
   cleanup
   prefetch
              Stream JSON changes from the source database and transform them to SQL
   catchup
              Apply prefetched changes from SQL files to the target database
              Create resources needed for pgcopydb
  + create
              Drop resources needed for pgcopydb
  + drop
  + sentinel
              Maintain a sentinel table on the source database
              Stream changes from the source database
   receive
   transform Transform changes from the source database into SOL commands
              Apply changes from the source database into the target database
   apply
 pgcopydb stream create
           Create a replication slot in the source database
   slot
   origin Create a replication origin in the target database
 pgcopydb stream drop
           Drop a replication slot in the source database
   slot
   origin Drop a replication origin in the target database
 pgcopydb stream sentinel
   create Create the sentinel table on the source database
   drop
           Drop the sentinel table on the source database
           Get the sentinel table values on the source database
   get
           Maintain a sentinel table on the source database
  + set
 pgcopydb stream sentinel set
   startpos Set the sentinel start position LSN on the source database
```

(continues on next page)

(continued from previous page)

endpos	Set the	sentinel	end position LSN on the source database
apply	Set the	sentinel	apply mode on the source database
prefetch	Set the	sentinel	prefetch mode on the source database

4.1.4 pgcopydb version

The pgcopydb version command outputs the version string of the version of pgcopydb used, and can do that in the JSON format when using the --json option.

```
$ pgcopydb version
pgcopydb version 0.8
compiled with PostgreSQL 12.12 on x86_64-apple-darwin16.7.0, compiled by Apple LLVM version 8.1.0 (clang-802.0.42), 64-bit
compatible with Postgres 10, 11, 12, 13, and 14
```

In JSON:

The details about the Postgres version applies to the version that's been used to build pgcopydb from sources, so that's the version of the client library libpq really.

4.2 pgcopydb clone

The main pgcopydb operation is the clone operation, and for historical and user friendlyness reasons three aliases are available that implement the same operation:

```
pgcopydb

clone Clone an entire database from source to target

fork Clone an entire database from source to target

copy-db Copy an entire database from source to target
```

4.2.1 pgcopydb clone

The command pgcopydb clone copies a database from the given source Postgres instance to the target Postgres instance.

pgcopydb clone: Clone an ent	ire database from source to target
usage: pgcopydb clonesou	rcetarget [table-jobsindex-jobs]
source	Postgres URI to the source database
target	Postgres URI to the target database
dir	Work directory to use
table-jobs	Number of concurrent COPY jobs to run
index-jobs	Number of concurrent CREATE INDEX jobs to run
split-tables-larger-than	Same-table concurrency size threshold
drop- if -exists	On the target database, clean-up from a previous run first
roles	Also copy roles found on source to target
no-owner	Do not set ownership of objects to match the original database
no-acl	Prevent restoration of access privileges (grant/revoke commands).
no-comments	Do not output commands to restore comments
skip-large-objects	Skip copying large objects (blobs)
skip-extensions	Skip restoring extensions
p	

(continues on next page)

	(continued from previous pugs	1
filters <filename></filename>	Use the filters defined in <filename></filename>	
restart	Allow restarting when temp files exist already	
resume	Allow resuming operations after a failure	
not -consistent	Allow taking a new snapshot on the source database	
snapshot	Use snapshot obtained with pg_export_snapshot	
follow	Implement logical decoding to replay changes	
slot-name	Use this Postgres replication slot name	
create-slot	Create the replication slot	
origin	Use this Postgres replication origin node name	
endpos	Stop replaying changes when reaching this LSN	

4.2.2 pgcopydb fork

The command pgcopydb fork copies a database from the given source Postgres instance to the target Postgres instance. This command is an alias to the command pgcopydb clone seen above.

4.2.3 pgcopydb copy-db

The command pgcopydb copy-db copies a database from the given source Postgres instance to the target Postgres instance. This command is an alias to the command pgcopydb clone seen above, and available for backward compatibility only.

Warning: The pgcopydb copy-db command is now deprecated and will get removed from pgcopydb when hitting version 1.0, please upgrade your scripts and integrations.

4.2.4 Description

The pgcopydb clone command implements both a base copy of a source database into a target database and also a full Logical Decoding client for the wal2json logical decoding plugin.

Base copy, or the clone operation

The pgcopydb clone command implements the following steps:

- 1. pgcopydb calls into pg_dump to produce the pre-data section and the post-data sections of the dump using Postgres custom format.
- 2. pgcopydb gets the list of ordinary and partitioned tables from a catalog query on the source database, and also the list of indexes, and the list of sequences with their current values.

When filtering is used, the list of objects OIDs that are meant to be filtered out is built during this step.

3. The pre-data section of the dump is restored on the target database using the pg_restore command, creating all the Postgres objects from the source database into the target database.

When filtering is used, the pg_restore --use-list feature is used to filter the list of objects to restore in this step.

4. Then as many as --table-jobs COPY sub-processes are started to share the workload and COPY the data from the source to the target database one table at a time, in a loop.

A Postgres connection and a SQL query to the Postgres catalog table pg_class is used to get the list of tables with data to copy around, and the *reltuples* statistic is used to start with the tables with the greatest number of rows first, as an attempt to minimize the copy time.

(continued from previous page)

5. An auxiliary process loops through all the Large Objects found on the source database and copies its data parts over to the target database, much like pg_dump itself would.

This step is much like pg_dump | pg_restore for large objects data parts, except that there isn't a good way to do just that with the tooling.

6. As many as --index-jobs CREATE INDEX sub-processes are started to share the workload and build indexes. In order to make sure to start the CREATE INDEX commands only after the COPY operation has completed, a queue mechanism is used. As soon as a table data COPY has completed, all the indexes for the table are queued for processing by the CREATE INDEX sub-processes.

The primary indexes are created as UNIQUE indexes at this stage.

- 7. Then the PRIMARY KEY constraints are created USING the just built indexes. This two-steps approach allows the primary key index itself to be created in parallel with other indexes on the same table, avoiding an EXCLUSIVE LOCK while creating the index.
- 8. As many as -table-jobs VACUUM ANALYZE sub-processes are started to share the workload. As soon as a table data COPY has completed, the table is queued for processing by the VACUUM ANALYZE sub-processes.
- 9. An auxilliary process is loops over the sequences on the source database and for each of them runs a separate query on the source to fetch the last_value and the is_called metadata the same way that pg_dump does.

For each sequence, pgcopydb then calls pg_catalog.setval() on the target database with the information obtained on the source database.

10. The final stage consists now of running the pg_restore command for the post-data section script for the whole database, and that's where the foreign key constraints and other elements are created.

The *post-data* script is filtered out using the pg_restore --use-list option so that indexes and primary key constraints already created in steps 6 and 7 are properly skipped now.

Postgres privileges, superuser, and dump and restore

Postgres has a notion of a superuser status that can be assigned to any role in the system, and the default role *postgres* has this status. From the Role Attributes documentation page we see that:

superuser status:

A database superuser bypasses all permission checks, except the right to log in. This is a dangerous privilege and should not be used carelessly; it is best to do most of your work as a role that is not a superuser. To create a new database superuser, use CREATE ROLE name SUPERUSER. You must do this as a role that is already a superuser.

Some Postgres objects can only be created by superusers, and some read and write operations are only allowed to superuser roles, such as the following non-exclusive list:

- Reading the pg_authid role password (even when encrypted) is restricted to roles with the superuser status. Reading this catalog table is done when calling pg_dumpall --roles-only so that the dump file can then be used to restore roles including their passwords.
- Most of the available Postgres extensions, at least when being written in C, are then only allowed to be created by roles with superuser status.

When such an extension contains Extension Configuration Tables and has been created with a role having superuser status, then the same superuser status is needed again to pg_dump and pg_restore that extension and its current configuration.

When using pgcopydb it is possible to split your migration in privileged and non-privileged parts, like in the following examples:

2

3

4 5

6

7

8 9

10

11

```
$ coproc ( pgcopydb snapshot )
# first two commands would use a superuser role to connect
$ pgcopydb copy roles --source ... --target ...
$ pgcopydb copy extensions --source ... --target ...
# now it's possible to use a non-superuser role to connect
$ pgcopydb clone --skip-extensions --source ... --target ...
$ kill -TERM ${COPROC_PID}
$ wait ${COPROC_PID}
```

In such a script, the calls to *pgcopydb copy roles* and *pgcopydb copy extensions* would be done with connection strings that connects with a role having superuser status; and then the call to *pgcopydb clone* would be done with a non-privileged role, typically the role that owns the source and target databases.

Warning: That said, there is currently a limitation in pg_dump that impacts pgcopydb. When an extension with configuration table has been installed as superuser, even the main pgcopydb clone operation has to be done with superuser status.

That's because pg_dump filtering (here, there --exclude-table option) does not apply to extension members, and pg_dump does not provide a mechanism to exclude extensions.

Change Data Capture using Postgres Logical Decoding

When using the --follow option the steps from the *pgcopydb follow* command are also run concurrently to the main copy. The Change Data Capture is then automatically driven from a prefetch-only phase to the prefetch-and-catchup phase, which is enabled as soon as the base copy is done.

See the command *pgcopydb stream sentinel set endpos* to remote control the follow parts of the command even while the command is already running.

The command *pgcopydb stream cleanup* must be used to free resources created to support the change data capture process.

Important: Make sure to read the documentation for *pgcopydb follow* and the specifics about Logical Replication Restrictions as documented by Postgres.

Change Data Capture Example 1

A simple approach to applying changes after the initial base copy has been done follows:

```
$ pgcopydb clone --follow &
# later when the application is ready to make the switch
$ pgcopydb stream sentinel set endpos --current
# later when the migration is finished, clean-up both source and target
$ pgcopydb stream cleanup
```

12

3 4

5

6

Change Data Capture Example 2

In some cases, it might be necessary to have more control over some of the steps taken here. Given pgcopydb flexibility, it's possible to implement the following steps:

1. Grab a snapshot from the source database and hold an open Postgres connection for the duration of the base copy.

In case of crash or other problems with the main operations, it's then possible to resume processing of the base copy and the applying of the changes with the same snapshot again.

This step is also implemented when using pgcopydb clone --follow. That said, if the command was interrupted (or crashed), then the snapshot would be lost.

2. Setup the logical decoding within the snapshot obtained in the previous step, and the replication tracking on the target database.

The following SQL objects are then created:

- a replication slot on the source database,
- a pgcopydb.sentinel table on the source database,
- a replication origin on the target database.

This step is also implemented when using pgcopydb clone --follow. There is no way to implement Change Data Capture with pgcopydb and skip creating those SQL objects.

- 3. Start the base copy of the source database, and prefetch logical decoding changes to ensure that we consume from the replication slot and allow the source database server to recycle its WAL files.
- 4. Remote control the apply process to stop consuming changes and applying them on the target database.
- 5. Re-sync the sequences to their now-current values.

Sequences are not handled by Postgres logical decoding, so extra care needs to be implemented manually here.

Important: The next version of pgcopydb will include that step in the pgcopydb clone --snapshot command automatically, after it stops consuming changes and before the process terminates.

- 6. Clean-up the specific resources created for supporting resumability of the whole process (replication slot on the source database, pgcopydb sentinel table on the source database, replication origin on the target database).
- 7. Stop holding a snaphot on the source database by stopping the pgcopydb snapshot process left running in the background.

If the command pgcopydb clone --follow fails it's then possible to start it again. It will automatically discover what was done successfully and what needs to be done again because it failed or was interrupted (table copy, index creation, resuming replication slot consuming, resuming applying changes at the right LSN position, etc).

Here is an example implement the previous steps:

```
$ pgcopydb snapshot &
$ pgcopydb stream setup
$ pgcopydb clone --follow &
# later when the application is ready to make the switch
$ pgcopydb stream sentinel set endpos --current
# when the follow process has terminated, re-sync the sequences
$ pgcopydb copy sequences
# later when the migration is finished, clean-up both source and target
$ pgcopydb stream cleanup
```

(continues on next page)

(continued from previous page)

now stop holding the snapshot transaction (adjust PID to your environment) $\$ kill $\$

4.2.5 Options

15 16 17

The following options are available to pgcopydb clone:

source	Connection string to the source Postgres instance. See the Postgres documentation for connection strings for the details. In short both the quoted form "host= dbname=" and the URI form postgres://user@host:5432/dbname are supported.
target	Connection string to the target Postgres instance.
dir	During its normal operations pgcopydb creates a lot of temporary files to track sub-processes progress. Temporary files are created in the directory location given by this option, or defaults to \${TMPDIR}/pgcopydb when the environment variable is set, or then to /tmp/pgcopydb.
table-jobs	How many tables can be processed in parallel.
	This limit only applies to the COPY operations, more sub-processes will be run- ning at the same time that this limit while the CREATE INDEX operations are in progress, though then the processes are only waiting for the target Postgres instance to do all the work.
index-jobs	How many indexes can be built in parallel, globally. A good option is to set this option to the count of CPU cores that are available on the Postgres target system, minus some cores that are going to be used for handling the COPY operations.
split-tables-larger-	than Allow <i>Same-table Concurrency</i> when processing the source database. This environment variable value is expected to be a byte size, and bytes units B, kB, MB, GB, TB, PB, and EB are known.
drop-if-exists	When restoring the schema on the target Postgres instance, pgcopydb actually uses pg_restore. When this options is specified, then the following pg_restore options are also used:cleanif-exists.
	This option is useful when the same command is run several times in a row, either to fix a previous mistake or for instance when used in a continuous integration system.
	This option causes DROP TABLE and DROP INDEX and other DROP commands to be used. Make sure you understand what you're doing here!
roles	The optionroles add a preliminary step that copies the roles found on the source instance to the target instance. As Postgres roles are global object, they do not exist only within the context of a specific database, so all the roles are copied over when using this option.
	The pg_dumpallroles-only is used to fetch the list of roles from the source database, and this command includes support for passwords. As a result, this operation requires the superuser privileges.
	See also pgcopydb copy roles.
no-owner	Do not output commands to set ownership of objects to match the original database. By default, pg_restore issues ALTER OWNER or SET SESSION

	AUTHORIZATION statements to set ownership of created schema elements. These statements will fail unless the initial connection to the database is made by a superuser (or the same user that owns all of the objects in the script). Withno-owner, any user name can be used for the initial connection, and this user will own all the created objects.
skip-large-objects	Skip copying large objects, also known as blobs, when copying the data from the source database to the target database.
skip-extensions	Skip copying extensions from the source database to the target database.
	When used, schema that extensions depend-on are also skipped: it is expected that creating needed extensions on the target system is then the responsibility of another command (such as <i>pgcopydb copy extensions</i>), and schemas that extensions depend-on are part of that responsibility.
	Because creating extensions require superuser, this allows a multi-steps approach where extensions are dealt with superuser privileges, and then the rest of the pg- copydb operations are done without superuser privileges.
filters <filename></filename>	This option allows to exclude table and indexes from the copy operations. See <i>Filtering</i> for details about the expected file format and the filtering options available.
restart	When running the pgcopydb command again, if the work directory already con- tains information from a previous run, then the command refuses to proceed and delete information that might be used for diagnostics and forensics.
	In that case, therestart option can be used to allow pgcopydb to delete traces from a previous run.
resume	When the pgcopydb command was terminated before completion, either by an interrupt signal (such as C-c or SIGTERM) or because it crashed, it is possible to resume the database migration.
	When resuming activity from a previous run, table data that was fully copied over to the target server is not sent again. Table data that was interrupted during the COPY has to be started from scratch even when usingresume: the COPY command in Postgres is transactional and was rolled back.
	Same reasonning applies to the CREATE INDEX commands and ALTER TABLE commands that pgcopydb issues, those commands are skipped on aresume run only if known to have run through to completion on the previous one.
	Finally, usingresume requires the use ofnot-consistent.
not-consistent	In order to be consistent, pgcopydb exports a Postgres snapshot by calling the pg_export_snapshot() function on the source database server. The snapshot is then re-used in all the connections to the source database server by using the SET TRANSACTION SNAPSHOT command.
	Per the Postgres documentation about pg_export_snapshot:
	Saves the transaction's current snapshot and returns a text string iden- tifying the snapshot. This string must be passed (outside the database) to clients that want to import the snapshot. The snapshot is available for import only until the end of the transaction that exported it.
	Now, when the pgcopydb process was interrupted (or crashed) on a previous run, it is possible to resume operations, but the snapshot that was exported does not exists anymore. The pgcopydb command can only resume operations with a new

	snapshot, and thus can not ensure consistency of the whole data set, because each run is now using their own snapshot.
snapshot	Instead of exporting its own snapshot by calling the PostgreSQL function pg_export_snapshot() it is possible for pgcopydb to re-use an already exported snapshot.
follow	When thefollow option is used then pgcopydb implements Change Data Capture as detailed in the manual page for <i>pgcopydb follow</i> in parallel to the main copy database steps.
	The replication slot is created using the same snapshot as the main database copy operation, and the changes to the source database are prefetched only during the initial copy, then prefetched and applied in a catchup process.
	It is possible to give pgcopydb clonefollow a termination point (the LSN endpos) while the command is running with the command <i>pgcopydb stream sentinel set endpos</i> .
slot-name	Logical replication slot to use. At the moment pgcopydb doesn't know how to create the logical replication slot itself. The slot should be created within the same transaction snapshot as the initial data copy.
	Must be using the wal2json output plugin, available with format-version 2.
create-slot	Instruct pgcopydb to create the logical replication slot to use.
endpos	Logical replication target LSN to use. Automatically stop replication and exit with normal exit status 0 when receiving reaches the specified LSN. If there's a record with LSN exactly equal to lsn, the record will be output.
	Theendpos option is not aware of transaction boundaries and may truncate output partway through a transaction. Any partially output transaction will not be consumed and will be replayed again when the slot is next read from. Individual messages are never truncated.
	See also documentation for pg_recvlogical.
origin	Logical replication target system needs to track the transactions that have been applied already, so that in case we get disconnected or need to resume operations we can skip already replayed transaction.
	Postgres uses a notion of an origin node name as documented in Replication Progress Tracking. This option allows to pick your own node name and defaults to "pgcopydb". Picking a different name is useful in some advanced scenarios like migrating several sources in the same target, where each source should have their own unique origin node name.
verbose	Increase current verbosity. The default level of verbosity is INFO. In ascending order pgcopydb knows about the following verbosity levels: FATAL, ERROR, WARN, INFO, NOTICE, DEBUG, TRACE.
debug	Set current verbosity to DEBUG level.
trace	Set current verbosity to TRACE level.
quiet	Set current verbosity to ERROR level.

4.2.6 Environment

PGCOPYDB_SOURCE_PGURI

Connection string to the source Postgres instance. When --source is ommitted from the command line, then this environment variable is used.

PGCOPYDB_TARGET_PGURI

Connection string to the target Postgres instance. When --target is ommitted from the command line, then this environment variable is used.

PGCOPYDB_TABLE_JOBS

Number of concurrent jobs allowed to run COPY operations in parallel. When --table-jobs is ommitted from the command line, then this environment variable is used.

PGCOPYDB_INDEX_JOBS

Number of concurrent jobs allowed to run CREATE INDEX operations in parallel. When --index-jobs is ommitted from the command line, then this environment variable is used.

PGCOPYDB_SPLIT_TABLES_LARGER_THAN

Allow *Same-table Concurrency* when processing the source database. This environment variable value is expected to be a byte size, and bytes units B, kB, MB, GB, TB, PB, and EB are known.

When --split-tables-larger-than is ommitted from the command line, then this environment variable is used.

PGCOPYDB_DROP_IF_EXISTS

When true (or *yes*, or *on*, or 1, same input as a Postgres boolean) then pgcopydb uses the pg_restore options --clean --if-exists when creating the schema on the target Postgres instance.

PGCOPYDB_SNAPSHOT

Postgres snapshot identifier to re-use, see also --snapshot.

TMPDIR

The pgcopydb command creates all its work files and directories in ${TMPDIR}/pgcopydb$, and defaults to /tmp/pgcopydb.

XDG_DATA_HOME

The standard XDG Base Directory Specification defines several environment variables that allow controling where programs should store their files.

XDG_DATA_HOME defines the base directory relative to which user-specific data files should be stored. If \$XDG_DATA_HOME is either not set or empty, a default equal to \$HOME/.local/share should be used.

When using Change Data Capture (through --follow option and Postgres logical decoding with wal2json) then pgcopydb pre-fetches changes in JSON files and transform them into SQL files to apply to the target database.

These files are stored at the following location, tried in this order:

- 1. when --dir is used, then pgcopydb uses the cdc subdirectory of the --dir location,
- 2. when XDG_DATA_HOME is set in the environment, then pgcopydb uses that location,
- 3. when neither of the previous settings have been used then pgcopydb defaults to using \${HOME}/. local/share.

4.2.7 Examples

\$ export PGCOPYDB_SOURCE_PGURI="port=54311 host=localhost dbname=pgloader" \$ export PGCOPYDB_TARGET_PGURI="port=54311 dbname=plop" \$ export PGCOPYDB DROP IF EXISTS=on \$ pqcopydb clone --table-jobs 8 --index-jobs 12 13:09:08 81987 INFO Running pgcopydb version 0.8.21.gacd2795.dirty from "/Applications/Postgres.app/Contents/Versions/12/bin/ ⊶pgcopvdb'' 13:09:08 81987 INFO [SOURCE] Copying database from "postgres://@:/pagila?" 13:09:08 81987 INFO [TARGET] Copying database into "postgres://@:/plop?" 13:09:08 81987 INFO Using work dir "/var/folders/d7/zzxmgs9s16gdxxcm0hs0sssw0000gn/T//pgcopydb" 13:09:08 81987 INFO Exported snapshot "00000003-00076012-1" from the source database 13:09:08 81991 INFO STEP 1: dump the source database schema (pre/post data) 13:09:08 81991 INF0 /Applications/Postgres.app/Contents/Versions/12/bin/pg_dump -Fc --snapshot 00000003-00076012-1 --section_ ->pre-data --file /var/folders/d7/zzxmgs9s16gdxxcm0hs0sssw0000gn/T//pgcopydb/schema/pre.dump 'postgres://@:/pagila?' 13:09:08 81991 INF0 /Applications/Postgres.app/Contents/Versions/12/bin/pg_dump -Fc --snapshot 00000003-00076012-1 --section_ ->post-data --file /var/folders/d7/zzxmgs9s16gdxxcm0hs0sssw0000gn/T//pgcopydb/schema/post.dump 'postgres://@:/pagila?' 13:09:08 81991 INFO STEP 2: restore the pre-data section to the target database 13:09:09 81991 INFO Listing ordinary tables in source database 13:09:09 81991 INFO Fetched information for 21 tables, with an estimated total of 46 248 tuples and 3776 kB 13:09:09 81991 INFO Fetching information for 13 sequences 13:09:09 81991 INF0 /Applications/Postgres.app/Contents/Versions/12/bin/pg_restore --dbname 'postgres://@:/plop?' --singlewhite the second $\hookrightarrow \texttt{folders/d7/zzxmgs9s16gdxxcm0hs0sssw0000gn/T//pgcopydb/schema/pre.dump}$ 13:09:09 81991 INFO STEP 3: copy data from source to target in sub-processes 13:09:09 81991 INFO STEP 4: create indexes and constraints in parallel 13:09:09 81991 INFO STEP 5: vacuum analyze each table 13:09:09 81991 INFO Now starting 8 processes 13:09:09 81991 INFO Reset sequences values on the target database 13:09:09 82003 INFO COPY "public"."rental" 13:09:09 82004 INFO COPY "public"."film" 13:09:09 82009 INFO COPY "public"."payment_p2020_04" 13:09:09 82002 INFO Copying large objects
 13:09:09
 82007
 INFO
 COPY
 public"."payment_p2020_03"

 13:09:09
 82010
 INFO
 COPY "public"."film_actor"

 13:09:09
 82005
 INFO
 COPY "public"."film_actor"

 13:09:09
 82005
 INFO
 COPY "public"."inventory"

 13:09:09
 82014
 INFO
 COPY "public"."inventory"
 13:09:09 82012 INFO COPY "public"."customer" 13:09:09 82009 INFO Creating 3 indexes for table "public"."payment_p2020_04" 13:09:09 82010 INFO Creating 2 indexes for table "public"."film_actor" 13:09:09 82007 INFO Creating 3 indexes for table "public"."payment_p2020_03" 13:09:09 82004 INFO Creating 5 indexes for table "public"."film" 13:09:09 82005 INFO Creating 2 indexes for table "public"."inventory 13:09:09 82033 INFO VACUUM ANALYZE "public"."payment_p2020_04"; 13:09:09 82036 INFO VACUUM ANALYZE "public"."film_actor"; 13:09:09 82039 INFO VACUUM ANALYZE "public"."payment_p2020_03"; 13:09:09 82041 INFO VACUUM ANALYZE "public"."film"; 13:09:09 82043 INFO VACUUM ANALYZE "public"."inventory"; . . . 13:09:09 81991 INFO STEP 7: restore the post-data section to the target database 13:09:09 81991 INF0 /Applications/Postgres.app/Contents/Versions/12/bin/pg_restore --dbname 'postgres://@:/plop?' --singlewhere the second $\hookrightarrow \texttt{folders/d7/zzxmgs9s16gdxxcm0hs0sssw0000gn/T//pgcopydb/schema/post.dump}$ Step Connection Duration Concurrency _____ ----- -----Dump Schema source 355ms 1 Prepare Schema target 135ms 1 COPY, INDEX, CONSTRAINTS, VACUUM (wall clock) both 641ms 8 + 12 COPY (cumulative) both 1s598 8 Large Objects (cumulative) both 29ms 1 CREATE INDEX, CONSTRAINTS (cumulative) target 4<072 12 366ms Finalize Schema target 1 ----------_____ Total Wall Clock Duration 1s499 8 + 12 both -----_____ _____ _____

4.3 pgcopydb follow

The command pgcopydb follow replays the database changes registered at the source database with the logical decoding pluing wal2json into the target database.

Important: While the pgcopydb follow is a full client for the logical decoding plugin wal2json, the general use case involves using pgcopydb clone --follow as documented in *Change Data Capture using Postgres Logical Decoding*.

When using Logical Decoding with pgcopydb or another tool, consider making sure you're familiar with the Logical Replication Restrictions that apply. In particular:

• DDL are not replicated.

When using DDL for partition scheme maintenance, such as when using the pg_partman extension, then consider creating a week or a month of partitions in advance, so that creating new partitions does not happen during the migration window.

• Sequence data is not replicated.

When using pgcopydb clone --follow (starting with pgcopydb version 0.9) then the sequence data is synced at the end of the operation, after the cutover point implemented via the *pgcopydb stream sentinel set endpos*.

Updating the sequences manually is also possible by running the command *pgcopydb copy sequences*.

• Large Objects are not replicated.

See the Postgres documentation page for Logical Replication Restrictions to read the exhaustive list of restrictions.

4.3.1 pgcopydb follow

```
pgcopydb follow: Replay changes from the source database to the target database
usage: pgcopydb follow
                        --source ... --target ..
                        Postgres URI to the source database
  --source
                        Postgres URI to the target database
  --target
  --dir
                        Work directory to use
  --filters <filename> Use the filters defined in <filename>
                        Allow restarting when temp files exist already
  --restart
                        Allow resuming operations after a failure
  --resume
                        Allow taking a new snapshot on the source database
  --not-consistent
                        Use snapshot obtained with pg_export_snapshot
  --snapshot
  --slot-name
                        Use this Postgres replication slot name
  --create-slot
                        Create the replication slot
  --origin
                        Use this Postgres replication origin node name
                        Stop replaying changes when reaching this LSN
  --endpos
```

4.3.2 Description

This command runs two concurrent subprocesses.

1. The first one pre-fetches the changes from the source database using the Postgres Logical Decoding protocol and save the JSON messages in local JSON files.

The logical decoding plugin wal2json must be available on the source database system.

Each time a JSON file is closed, an auxilliary process is started to transform the JSON file into a matching SQL file. This processing is done in the background, and the main receiver process only waits for the transformation process to be finished when there is a new JSON file to transform.

In other words, only one such transform process can be started in the background, and the process is blocking when a second one could get started.

The design model here is based on the assumption that receiving the next set of JSON messages that fills-up a whole JSON file is going to take more time than transforming the JSON file into an SQL file. When that assumption proves wrong, consider opening an issue on the github project for pgcopydb.

2. The second process catches-up with changes happening on the source database by applying the SQL files to the target database system.

The Postgres API for Replication Progress Tracking is used in that process so that we can skip already applied transactions at restart or resume.

It is possible to start the pgcopydb follow command and then later, while it's still running, set the LSN for the end position with the same effect as using the command line option --endpos, or switch from prefetch mode only to prefetch and catchup mode. For that, see the commands *pgcopydb stream sentinel set endpos*, *pgcopydb stream sentinel set apply*, and *pgcopydb stream sentinel set prefetch*.

Note that in many case the --endpos LSN position is not known at the start of this command. Also before entering the *prefetch and apply* mode it is important to make sure that the initial base copy is finished.

Finally, it is also possible to setup the streaming replication options before using the pgcopydb follow command: see the *pgcopydb stream setup* and *pgcopydb stream cleanup* commands.

4.3.3 Replica Identity and lack of Primary Keys

Postgres Logical Decoding works with replaying changes using SQL statements, and for that exposes the concept of *Replica Identity* as described in the documentation for the ALTER TABLE ... REPLICA IDENTITY command.

To quote Postgres docs:

This form changes the information which is written to the write-ahead log to identify rows which are updated or deleted. In most cases, the old value of each column is only logged if it differs from the new value; however, if the old value is stored externally, it is always logged regardless of whether it changed. This option has no effect except when logical replication is in use.

To support Change Data Capture with Postgres Logical Decoding for tables that do not have a Primary Key, then it is necessary to use the ALTER TABLE ... REPLICA IDENTITY command for those tables.

In practice the two following options are to be considered:

• REPLICA IDENTITY USING INDEX index_name

This form is prefered when a UNIQUE index exists for the table without a primary key. The index must be unique, not partial, not deferrable, and include only columns marked NOT NULL.

• REPLICA IDENTITY FULL

When this is used on a table, then the WAL records contain the old values of all columns in the row.

4.3.4 Logical Decoding Pre-Fetching

When using pgcopydb clone --follow a logical replication slot is created on the source database before the initial COPY, using the same Postgres snapshot. This ensure data consistency.

Within the pgcopydb clone --follow approach, it is only possible to start applying the changes from the source database after the initial COPY has finished on the target database.

Also, from the Postgres documentation we read that Postgres replication slots provide an automated way to ensure that the primary does not remove WAL segments until they have been received by all standbys.

Accumulating WAL segments on the primary during the whole duration of the initial COPY involves capacity hazards, which translate into potential *File System is Full* errors on the WAL disk of the source database. It is crucial to avoid such a situation.

This is why pgcopydb implements CDC pre-fetching. In parallel to the initial COPY the command pgcopydb clone --follow pre-fetches the changes in local JSON and SQL files. Those files are placed in the XDG_DATA_HOME location, which could be a mount point for an infinite Blob Storage area.

The pgcopydb follow command is a convenience command that's available as a logical decoding client for the wal2json plugin, and it shares the same implementation as the pgcopydb clone --follow command. As a result, the pre-fetching strategy is also relevant to the pgcopydb follow command.

4.3.5 The sentinel table, or the Remote Control

To track progress and allow resuming of operations, pgcopydb uses a sentinel table on the source database. The sentinel table consists of a single row with the following fields:

```
$ pgcopydb stream sentinel get
startpos 1/8D173AF8
endpos 0/0
apply disabled
write_lsn 0/0
flush_lsn 0/0
replay lsn 0/0
```

Note that you can use the command pgcopydb stream sentinel get --json to fetch a JSON formatted output, such as the following:

```
{
   "startpos": "1/8D173AF8",
   "endpos": "1/8D173AF8",
   "apply": false,
   "write_lsn": "0/0",
   "flush_lsn": "0/0",
   "replay_lsn": "0/0"
```

The first three fields (startpos, endpos, apply) are specific to pgcopydb, then the following three fields (write_lsn, flush_lsn, replay_lsn) follow the Postgres replication protocol as visible in the docs for the pg_stat_replication function.

startpos

The startpos field is the current LSN on the source database at the time when the Change Data Capture is setup in pgcopydb, such as when using the *pgcopydb stream setup* command.

Note that both the pgcopydb follow and the pgcopydb clone --follow command implement the setup parts if the pgcopydb stream setup has not been used already.

endpos

The endpos field is last LSN position from the source database that pgcopydb replays. The command pgcopydb follow (or pgcopydb clone --follow) stops when reaching beyond this LSN position.

The endpos can be set at the start of the process, which is useful for unit testing, or while the command is running, which is useful in production to define a cutover point.

To define the endpos while the command is running, use pgcopydb stream sentinel set endpos.

• apply

The apply field is a boolean (enabled/disabled) that control the catchup process. The pgcopydb catchup process replays the changes only when the apply boolean is set to true.

The pgcopydb clone --follow command automatically enables the apply field of the sentinel table as soon as the initial COPY is done.

To manually control the apply field, use the pgcopydb stream sentinel set apply command.

write_lsn

The Postgres documentation for pg_stat_replication.write_lsn is: Last write-ahead log location written to disk by this standby server.

In the pgcopydb case, the sentinel field write_lsn is the position that has been written to disk (as JSON) by the streaming process.

• flush_lsn

The Postgres documentation for pg_stat_replication.flush_lsn is: Last write-ahead log location flushed to disk by this standby server

In the pgcopydb case, the sentinel field flush_lsn is the position that has been written and then fsync'ed to disk (as JSON) by the streaming process.

replay_lsn

The Postgres documentation for pg_stat_replication.replay_lsn is: Last write-ahead log location replayed into the database on this standby server

In the pgcopydb case, the sentinel field replay_lsn is the position that has been applied to the target database, as kept track from the WAL.json and then the WAL.sql files, and using the Postgres API for Replication Progress Tracking.

The replay_lsn is also shared by the pgcopydb streaming process that uses the Postgres logical replication protocol, so the pg_stat_replication entry associated with the replication slot used by pgcopydb can be used to monitor replication lag.

As the pgcopydb streaming processes maintain the sentinel table on the source database, it is also possible to use it to keep track of the logical replication progress.

4.3.6 Options

The following options are available to pgcopydb follow:

source	Connection string to the source Postgres instance. See the Postgres documentation for connection strings for the details. In short both the quoted form "host= dbname=" and the URI form postgres://user@host:5432/dbname are supported.
target	Connection string to the target Postgres instance.
dir	During its normal operations pgcopydb creates a lot of temporary files to track sub-processes progress. Temporary files are created in the directory location given by this option, or defaults to \${TMPDIR}/pgcopydb when the environment variable is set, or then to /tmp/pgcopydb.

restart	When running the pgcopydb command again, if the work directory already con- tains information from a previous run, then the command refuses to proceed and delete information that might be used for diagnostics and forensics.
	In that case, therestart option can be used to allow pgcopydb to delete traces from a previous run.
resume	When the pgcopydb command was terminated before completion, either by an interrupt signal (such as C-c or SIGTERM) or because it crashed, it is possible to resume the database migration.
	When resuming activity from a previous run, table data that was fully copied over to the target server is not sent again. Table data that was interrupted during the COPY has to be started from scratch even when usingresume: the COPY command in Postgres is transactional and was rolled back.
	Same reasonning applies to the CREATE INDEX commands and ALTER TABLE commands that pgcopydb issues, those commands are skipped on aresume run only if known to have run through to completion on the previous one.
	Finally, usingresume requires the use ofnot-consistent.
not-consistent	In order to be consistent, pgcopydb exports a Postgres snapshot by calling the pg_export_snapshot() function on the source database server. The snapshot is then re-used in all the connections to the source database server by using the SET TRANSACTION SNAPSHOT command.
	Per the Postgres documentation about pg_export_snapshot:
	Saves the transaction's current snapshot and returns a text string iden- tifying the snapshot. This string must be passed (outside the database) to clients that want to import the snapshot. The snapshot is available for import only until the end of the transaction that exported it.
	Now, when the pgcopydb process was interrupted (or crashed) on a previous run, it is possible to resume operations, but the snapshot that was exported does not exists anymore. The pgcopydb command can only resume operations with a new snapshot, and thus can not ensure consistency of the whole data set, because each run is now using their own snapshot.
snapshot	Instead of exporting its own snapshot by calling the PostgreSQL function pg_export_snapshot() it is possible for pgcopydb to re-use an already exported snapshot.
slot-name	Logical replication slot to use. At the moment pgcopydb doesn't know how to create the logical replication slot itself. The slot should be created within the same transaction snapshot as the initial data copy.
	Must be using the wal2json output plugin, available with format-version 2.
create-slot	Instruct pgcopydb to create the logical replication slot to use.
endpos	Logical replication target LSN to use. Automatically stop replication and exit with normal exit status 0 when receiving reaches the specified LSN. If there's a record with LSN exactly equal to lsn, the record will be output.
	Theendpos option is not aware of transaction boundaries and may truncate output partway through a transaction. Any partially output transaction will not be consumed and will be replayed again when the slot is next read from. Individual messages are never truncated.
	See also documentation for pg_recvlogical.

origin	Logical replication target system needs to track the transactions that have been applied already, so that in case we get disconnected or need to resume operations we can skip already replayed transaction.
	Postgres uses a notion of an origin node name as documented in Replication Progress Tracking. This option allows to pick your own node name and defaults to "pgcopydb". Picking a different name is useful in some advanced scenarios like migrating several sources in the same target, where each source should have their own unique origin node name.
verbose	Increase current verbosity. The default level of verbosity is INFO. In ascending order pgcopydb knows about the following verbosity levels: FATAL, ERROR, WARN, INFO, NOTICE, DEBUG, TRACE.
debug	Set current verbosity to DEBUG level.
trace	Set current verbosity to TRACE level.
quiet	Set current verbosity to ERROR level.

4.3.7 Environment

PGCOPYDB_SOURCE_PGURI

Connection string to the source Postgres instance. When --source is ommitted from the command line, then this environment variable is used.

PGCOPYDB_TARGET_PGURI

Connection string to the target Postgres instance. When --target is ommitted from the command line, then this environment variable is used.

PGCOPYDB_SNAPSHOT

Postgres snapshot identifier to re-use, see also --snapshot.

TMPDIR

The pgcopydb command creates all its work files and directories in ${TMPDIR}/pgcopydb$, and defaults to /tmp/pgcopydb.

XDG_DATA_HOME

The standard XDG Base Directory Specification defines several environment variables that allow controling where programs should store their files.

XDG_DATA_HOME defines the base directory relative to which user-specific data files should be stored. If \$XDG_DATA_HOME is either not set or empty, a default equal to \$HOME/.local/share should be used.

When using Change Data Capture (through -- follow option and Postgres logical decoding with wal2json) then pgcopydb pre-fetches changes in JSON files and transform them into SQL files to apply to the target database.

These files are stored at the following location, tried in this order:

- 1. when --dir is used, then pgcopydb uses the cdc subdirectory of the --dir location,
- 2. when XDG_DATA_HOME is set in the environment, then pgcopydb uses that location,
- 3. when neither of the previous settings have been used then pgcopydb defaults to using \${HOME}/. local/share.

4.4 pgcopydb snapshot

pgcopydb snapshot - Create and exports a snapshot on the source database

The command pgcopydb snapshot connects to the source database and executes a SQL query to export a snapshot. The obtained snapshot is both printed on stdout and also in a file where other pgcopydb commands might expect to find it.

```
pgcopydb snapshot: Create and exports a snapshot on the source database
usage: pgcopydb snapshot --source ...
--source --source Postgres URI to the source database
--dir Work directory to use
```

4.4.1 Options

The following options are available to pgcopydb create and pgcopydb drop subcommands:

source	Connection string to the source Postgres instance. See the Postgres documentation for connection strings for the details. In short both the quoted form "host= dbname=" and the URI form postgres://user@host:5432/dbname are supported.
dir	During its normal operations pgcopydb creates a lot of temporary files to track sub-processes progress. Temporary files are created in the directory location given by this option, or defaults to \${TMPDIR}/pgcopydb when the environment variable is set, or then to /tmp/pgcopydb.
snapshot	Instead of exporting its own snapshot by calling the PostgreSQL function pg_export_snapshot() it is possible for pgcopydb to re-use an already exported snapshot.
slot-name	Logical replication slot name to use, default to pgcopydb. The slot should be created within the same transaction snapshot as the initial data copy.
	Must be using the wal2json output plugin, available with format-version 2.
origin	Logical replication target system needs to track the transactions that have been applied already, so that in case we get disconnected or need to resume operations we can skip already replayed transaction.
	Postgres uses a notion of an origin node name as documented in Replication Progress Tracking. This option allows to pick your own node name and defaults to "pgcopydb". Picking a different name is useful in some advanced scenarios like migrating several sources in the same target, where each source should have their own unique origin node name.
startpos	Logical replication target system registers progress by assigning a current LSN to theorigin node name. When creating an origin on the target database system, it is required to provide the current LSN from the source database system, in order to properly bootstrap pgcopydb logical decoding.
verbose	Increase current verbosity. The default level of verbosity is INFO. In ascending order pgcopydb knows about the following verbosity levels: FATAL, ERROR, WARN, INFO, NOTICE, DEBUG, TRACE.
debug	Set current verbosity to DEBUG level.
trace	Set current verbosity to TRACE level.

--quiet

Set current verbosity to ERROR level.

4.4.2 Environment

PGCOPYDB_SOURCE_PGURI

Connection string to the source Postgres instance. When --source is ommitted from the command line, then this environment variable is used.

4.4.3 Examples

Create a snapshot on the source database in the background:

```
$ pgcopydb snapshot &
[1] 72938
17:31:52 72938 INF0 Running pgcopydb version 0.7.13.gcbf2d16.dirty from "/Users/dim/dev/PostgreSQL/pgcopydb/./src/bin/
-pgcopydb/pgcopydb"
17:31:52 72938 INF0 Using work dir "/var/folders/d7/zzxmg59s16gdxxcm0hs0sssw0000gn/T//pgcopydb"
17:31:52 72938 INF0 Removing the stale pid file "/var/folders/d7/zzxmg59s16gdxxcm0hs0sssw0000gn/T//pgcopydb/pgcopydb.aux.pid"
17:31:52 72938 INF0 Work directory "/var/folders/d7/zzxmg59s16gdxxcm0hs0sssw0000gn/T//pgcopydb"
17:31:52 72938 INF0 Exported snapshot "00000003-000CB5FE-1" from the source database
00000003-000CB5FE-1
```

And when the process is done, stop maintaining the snapshot in the background:

```
$ kill %1
17:31:56 72938 INFO Asked to terminate, aborting
[1]+ Done pgcopydb snapshot
```

4.5 pgcopydb copy

pgcopydb copy - Implement the data section of the database copy

This command prefixes the following sub-commands:

```
pgcopydb copy
 db
               Copy an entire database from source to target
 roles
               Copy the roles from the source instance to the target instance
  extensions
               Copy the extensions from the source instance to the target instance
               Copy the database schema from source to target
  schema
  data
               Copy the data section from source to target
  table-data
               Copy the data from all tables in database from source to target
  blobs
               Copy the blob data from ther source database to the target
               Copy the current value from all sequences in database from source to target
  sequences
  indexes
               Create all the indexes found in the source database in the target
  constraints
              Create all the constraints found in the source database in the target
```

Those commands implement a part of the whole database copy operation as detailed in section *pgcopydb clone*. Only use those commands to debug a specific part, or because you know that you just want to implement that step.

Warning: Using the pgcopydb clone command is strongly advised. This mode of operations is useful for debugging and advanced use cases only.
4.5.1 pgcopydb copy db

pgcopydb copy db - Copy an entire database from source to target

The command pgcopydb copy db is an alias for pgcopydb clone. See also pgcopydb clone.

```
pgcopydb copy db: Copy an entire database from source to target
usage: pgcopydb copy db
                                      --target ... [ --table-jobs ... --index-jobs ... ]
                         --source ...
  --source
                        Postgres URI to the source database
                        Postgres URI to the target database
  --target
  --dir
                        Work directory to use
  --table-jobs
                        Number of concurrent COPY jobs to run
  --index-jobs
                        Number of concurrent CREATE INDEX jobs to run
  --drop-if-exists
                        On the target database, clean-up from a previous run first
                        Also copy roles found on source to target
  --roles
  --no-owner
                        Do not set ownership of objects to match the original database
                        Prevent restoration of access privileges (grant/revoke commands)
  --no-acl
  --no-comments
                        Do not output commands to restore comments
  --skip-large-objects Skip copying large objects (blobs)
  --filters <filename> Use the filters defined in <filename>
                        Allow restarting when temp files exist already
  --restart
                        Allow resuming operations after a failure
  --resume
  --not-consistent
                        Allow taking a new snapshot on the source database
  --snapshot
                        Use snapshot obtained with pg_export_snapshot
```

4.5.2 pgcopydb copy roles

pgcopydb copy roles - Copy the roles from the source instance to the target instance

The command pgcopydb copy roles implements both *pgcopydb dump roles* and then *pgcopydb restore roles*.

```
pgcopydb copy roles: Copy the roles from the source instance to the target instance
usage: pgcopydb copy roles --source ... --target ...
--source Postgres URI to the source database
--target Postgres URI to the target database
--dir Work directory to use
```

Note: In Postgres, roles are a global object. This means roles do not belong to any specific database, and as a result, even when the pgcopydb tool otherwise works only in the context of a specific database, this command is not limited to roles that are used within a single database.

When a role already exists on the target database, its restoring is entirely skipped, which includes skipping both the CREATE ROLE and the ALTER ROLE commands produced by pg_dumpall --roles-only.

The pg_dumpall --roles-only is used to fetch the list of roles from the source database, and this command includes support for passwords. As a result, this operation requires the superuser privileges.

4.5.3 pgcopydb copy extensions

pgcopydb copy extensions - Copy the extensions from the source instance to the target instance

The command pgcopydb copy extensions gets a list of the extensions installed on the source database, and for each of them run the SQL command CREATE EXTENSION IF NOT EXISTS.

```
pgcopydb copy extensions: Copy the extensions from the source instance to the target instance
usage: pgcopydb copy extensions --source ... --target ...
--source Postgres URI to the source database
--target Postgres URI to the target database
--dir Work directory to use
```

When copying extensions, this command also takes care of copying any Extension Configuration Tables user-data to the target database.

4.5.4 pgcopydb copy schema

pgcopydb copy schema - Copy the database schema from source to target

The command pgcopydb copy schema implements the schema only section of the clone steps.

```
pgcopydb copy schema: Copy the database schema from source to target
usage: pgcopydb copy schema
                            --source ... --target ... [ --table-jobs ... --index-jobs ... ]
                        Postgres URI to the source database
  --source
 --target
                        Postgres URI to the target database
 --dir
                        Work directory to use
 --filters <filename> Use the filters defined in <filename>
                        Allow restarting when temp files exist already
  --restart
  --resume
                        Allow resuming operations after a failure
  --not-consistent
                        Allow taking a new snapshot on the source database
  --snapshot
                        Use snapshot obtained with pg_export_snapshot
```

4.5.5 pgcopydb copy data

pgcopydb copy data - Copy the data section from source to target

The command pgcopydb copy data implements the data section of the clone steps.

```
pgcopydb copy data: Copy the data section from source to target
usage: pgcopydb copy data
                           --source ... --target ... [ --table-jobs ... --index-jobs ... ]
                        Postgres URI to the source database
  --source
  --target
                        Postgres URI to the target database
 --dir
                        Work directory to use
 --table-jobs
                        Number of concurrent COPY jobs to run
  --index-jobs
                        Number of concurrent CREATE INDEX jobs to run
  --drop-if-exists
                        On the target database, clean-up \ensuremath{\textit{from a}} previous run first
  --no-owner
                        Do not set ownership of objects to match the original database
  --skip-large-objects Skip copying large objects (blobs)
 --restart
                        Allow restarting when temp files exist already
  --resume
                        Allow resuming operations after a failure
                        Allow taking a new snapshot on the source database
  --not-consistent
  --snapshot
                        Use snapshot obtained with pg_export_snapshot
```

Note: The current command line has both the commands pgcopydb copy table-data and pgcopydb copy data, which are looking quite similar but implement different steps. Be careful for now. This will change later.

The pgcopydb copy data command implements the following steps:

- \$ pgcopydb copy table-data
 \$ pgcopydb copy blobs
 \$ pgcopydb copy indexes
 \$ pgcopydb copy constraints
- \$ pgcopydb copy constraints
 \$ pgcopydb copy sequences
- \$ vacuumdb -z

Those steps are actually done concurrently to one another when that's possible, in the same way as the main command pgcopydb clone would. The only difference is that the pgcopydb clone command also prepares and finishes the schema parts of the operations (pre-data, then post-data), which the pgcopydb copy data command ignores.

4.5.6 pgcopydb copy table-data

pgcopydb copy table-data - Copy the data from all tables in database from source to target

The command pgcopydb copy table-data fetches the list of tables from the source database and runs a COPY TO command on the source database and sends the result to the target database using a COPY FROM command directly, avoiding disks entirely.

```
pgcopydb copy table-data: Copy the data from all tables in database from source to target
usage: pgcopydb copy table-data --source ... --target ... [ --table-jobs ... --index-jobs ... ]
                    Postgres URI to the source database
  --source
 --target
                    Postgres URI to the target database
                    Work directory to use
 --dir
  --table-jobs
                    Number of concurrent COPY jobs to run
  --restart
                    Allow restarting when temp files exist already
                    Allow resuming operations after a failure
  --resume
  --not-consistent
                    Allow taking a new snapshot on the source database
  --snapshot
                    Use snapshot obtained with pg_export_snapshot
```

4.5.7 pgcopydb copy blobs

pgcopydb copy blobs - Copy the blob data from ther source database to the target

The command pgcopydb copy blobs fetches list of large objects (aka blobs) from the source database and copies their data parts to the target database. By default the command assumes that the large objects metadata have already been taken care of, because of the behaviour of pg_dump --section=pre-data.

```
pgcopydb copy blobs: Copy the blob data from ther source database to the target
usage: pgcopydb copy blobs --source ... --target ...
                    Postgres URI to the source database
  --source
  --target
                    Postgres URI to the target database
                    Work directory to use
  --dir
                    Allow restarting when temp files exist already
  --restart
                    Allow resuming operations after a failure
  --resume
  --not-consistent Allow taking a new snapshot on the source database
                    Use snapshot obtained with pg_export_snapshot
  --snapshot
  --drop-if-exists On the target database, drop and create large objects
```

4.5.8 pgcopydb copy sequences

pgcopydb copy sequences - Copy the current value from all sequences in database from source to target

The command pgcopydb copy sequences fetches the list of sequences from the source database, then for each sequence fetches the last_value and is_called properties the same way pg_dump would on the source database, and then for each sequence call pg_catalog.setval() on the target database.

```
pgcopydb copy sequences: Copy the current value from all sequences in database from source to target
usage: pgcopydb copy sequences --source ... --target ... [ --table-jobs ... --index-jobs ... ]
--source Postgres URI to the source database
--target Postgres URI to the target database
--dir Work directory to use
--restart Allow restarting when temp files exist already
--resume Allow resuming operations after a failure
--not-consistent Allow taking a new snapshot on the source database
```

4.5.9 pgcopydb copy indexes

pgcopydb copy indexes - Create all the indexes found in the source database in the target

The command pgcopydb copy indexes fetches the list of indexes from the source database and runs each index CREATE INDEX statement on the target database. The statements for the index definitions are modified to include IF NOT EXISTS and allow for skipping indexes that already exist on the target database.

```
pgcopydb copy indexes: Create all the indexes found in the source database in the target
usage: pgcopydb copy indexes --source ... --target ... [ --table-jobs ... --index-jobs ... ]
--source Postgres URI to the source database
--target Postgres URI to the target database
--dir Work directory to use
--index-jobs Number of concurrent CREATE INDEX jobs to run
--restart Allow restarting when temp files exist already
--resume Allow resuming operations after a failure
--not-consistent Allow taking a new snapshot on the source database
```

4.5.10 pgcopydb copy constraints

pgcopydb copy constraints - Create all the constraints found in the source database in the target

The command pgcopydb copy constraints fetches the list of indexes from the source database and runs each index ALTER TABLE ... ADD CONSTRAINT ... USING INDEX statement on the target database.

The indexes must already exist, and the command will fail if any constraint is found existing already on the target database.

```
pgcopydb copy indexes: Create all the indexes found in the source database in the target
usage: pgcopydb copy indexes --source ... --target ... [ --table-jobs ... --index-jobs ... ]
--source Postgres URI to the source database
--target Postgres URI to the target database
--dir Work directory to use
--restart Allow restarting when temp files exist already
--resume Allow resuming operations after a failure
--not-consistent Allow taking a new snapshot on the source data
```

4.5.11 Description

These commands allow implementing a specific step of the pgcopydb operations at a time. It's useful mainly for debugging purposes, though some advanced and creative usage can be made from the commands.

The target schema is not created, so it needs to have been taken care of first. It is possible to use the commands *pgcopydb dump schema* and then *pgcopydb restore pre-data* to prepare your target database.

To implement the same operations as a pgcopydb clone command would, use the following recipe:

```
$ export PGCOPYDB_SOURCE_PGURI="postgres://user@source/dbname"
$ export PGCOPYDB_TARGET_PGURI="postgres://user@target/dbname"
$ pgcopydb dump schema
$ pgcopydb restore pre-data --resume --not-consistent
$ pgcopydb copy table-data --resume --not-consistent
$ pgcopydb copy sequences --resume --not-consistent
$ pgcopydb copy indexes --resume --not-consistent
$ pgcopydb copy constraints --resume --not-consistent
$ yaccumdb -z
$ pgcopydb restore post-data --resume --not-consistent
```

The main pgcopydb clone is still better at concurrency than doing those steps manually, as it will create the indexes for any given table as soon as the table-data section is finished, without having to wait until the last table-data has been copied over. Same applies to constraints, and then vacuum analyze.

4.5.12 Options

The following options are available to pgcopydb copy sub-commands:

source	Connection string to the source Postgres instance. See the Postgres documentation for connection strings for the details. In short both the quoted form "host= dbname=" and the URI form postgres://user@host:5432/dbname are supported.
target	Connection string to the target Postgres instance.
dir	During its normal operations pgcopydb creates a lot of temporary files to track sub-processes progress. Temporary files are created in the directory location given by this option, or defaults to \${TMPDIR}/pgcopydb when the environment variable is set, or then to /tmp/pgcopydb.
table-jobs	How many tables can be processed in parallel.
	This limit only applies to the COPY operations, more sub-processes will be run- ning at the same time that this limit while the CREATE INDEX operations are in progress, though then the processes are only waiting for the target Postgres instance to do all the work.
index-jobs	How many indexes can be built in parallel, globally. A good option is to set this option to the count of CPU cores that are available on the Postgres target system, minus some cores that are going to be used for handling the COPY operations.
split-tables-larger-	than Allow <i>Same-table Concurrency</i> when processing the source database. This environment variable value is expected to be a byte size, and bytes units B, kB, MB, GB, TB, PB, and EB are known.
skip-large-objects	Skip copying large objects, also known as blobs, when copying the data from the source database to the target database.
restart	When running the pgcopydb command again, if the work directory already con- tains information from a previous run, then the command refuses to proceed and delete information that might be used for diagnostics and forensics.
	In that case, therestart option can be used to allow pgcopydb to delete traces from a previous run.
resume	When the pgcopydb command was terminated before completion, either by an interrupt signal (such as C-c or SIGTERM) or because it crashed, it is possible to resume the database migration.
	When resuming activity from a previous run, table data that was fully copied over to the target server is not sent again. Table data that was interrupted during the COPY has to be started from scratch even when usingresume: the COPY command in Postgres is transactional and was rolled back.
	Same reasonning applies to the CREATE INDEX commands and ALTER TABLE commands that pgcopydb issues, those commands are skipped on aresume run only if known to have run through to completion on the previous one.
	Finally, usingresume requires the use ofnot-consistent.
not-consistent	In order to be consistent, pgcopydb exports a Postgres snapshot by calling the pg_export_snapshot() function on the source database server. The snapshot is then re-used in all the connections to the source database server by using the SET TRANSACTION SNAPSHOT command.
	Per the Postgres documentation about pg_export_snapshot:

	Saves the transaction's current snapshot and returns a text string iden- tifying the snapshot. This string must be passed (outside the database) to clients that want to import the snapshot. The snapshot is available for import only until the end of the transaction that exported it.
	Now, when the pgcopydb process was interrupted (or crashed) on a previous run, it is possible to resume operations, but the snapshot that was exported does not exists anymore. The pgcopydb command can only resume operations with a new snapshot, and thus can not ensure consistency of the whole data set, because each run is now using their own snapshot.
snapshot	Instead of exporting its own snapshot by calling the PostgreSQL function pg_export_snapshot() it is possible for pgcopydb to re-use an already exported snapshot.
verbose	Increase current verbosity. The default level of verbosity is INFO. In ascending order pgcopydb knows about the following verbosity levels: FATAL, ERROR, WARN, INFO, NOTICE, DEBUG, TRACE.
debug	Set current verbosity to DEBUG level.
trace	Set current verbosity to TRACE level.
quiet	Set current verbosity to ERROR level.

4.5.13 Environment

PGCOPYDB_SOURCE_PGURI

Connection string to the source Postgres instance. When --source is ommitted from the command line, then this environment variable is used.

PGCOPYDB_TARGET_PGURI

Connection string to the target Postgres instance. When --target is ommitted from the command line, then this environment variable is used.

PGCOPYDB_TABLE_JOBS

Number of concurrent jobs allowed to run COPY operations in parallel. When --table-jobs is ommitted from the command line, then this environment variable is used.

PGCOPYDB_INDEX_JOBS

Number of concurrent jobs allowed to run CREATE INDEX operations in parallel. When --index-jobs is ommitted from the command line, then this environment variable is used.

PGCOPYDB_SPLIT_TABLES_LARGER_THAN

Allow *Same-table Concurrency* when processing the source database. This environment variable value is expected to be a byte size, and bytes units B, kB, MB, GB, TB, PB, and EB are known.

When --split-tables-larger-than is ommitted from the command line, then this environment variable is used.

PGCOPYDB_DROP_IF_EXISTS

When true (or *yes*, or *on*, or 1, same input as a Postgres boolean) then pgcopydb uses the pg_restore options --clean --if-exists when creating the schema on the target Postgres instance.

PGCOPYDB_SNAPSHOT

Postgres snapshot identifier to re-use, see also --snapshot.

TMPDIR

The pgcopydb command creates all its work files and directories in {TMPDIR}/pgcopydb, and defaults to /tmp/pgcopydb.

4.5.14 Examples

Let's export the Postgres databases connection strings to make it easy to re-use them all along:

```
$ export PGCOPYDB_SOURCE_PGURI="port=54311 host=localhost dbname=pgloader"
$ export PGCOPYDB_TARGET_PGURI="port=54311 dbname=plop"
```

Now, first dump the schema:

Now restore the pre-data schema on the target database, cleaning up the already existing objects if any, which allows running this test scenario again and again. It might not be what you want to do in your production target instance though!

```
PGCOPYDB_DROP_IF_EXISTS=on pgcopydb restore pre-data --no-owner

15:24:29 75591 INF0 Removing the stale pid file "/tmp/pgcopydb/pgcopydb.pid"

15:24:29 75591 INF0 Restoring database from "/tmp/pgcopydb"

15:24:29 75591 INF0 Restoring database into "port=54311 dbname=plop"

15:24:29 75591 INF0 Using pg_restore for Postgres "12.9" at "/Applications/Postgres.app/Contents/Versions/12/bin/pg_restore"

15:24:29 75591 INF0 /Applications/Postgres.app/Contents/Versions/12/bin/pg_restore --dbname 'port=54311 dbname=plop' --clean_

--if-exists --no-owner /tmp/pgcopydb/schema/pre.dump
```

Then copy the data over:

<pre>\$ pgcopydb copy tabl</pre>	<pre>\$ pgcopydb copy table-dataresumenot-consistent</pre>					
15:24:36 75688 INFO [SOURCE] Copying database from "port=54311 host=localhost dbname=pgloader"						
15:24:36 75688 INFO	15:24:36 75688 INFO [TARGET] Copying database into "port=54311 dbname=plop"					
15:24:36 75688 INFO	Removing the stale pid file	e "/tmp/pgcopy	/db/pgcopydb	.pid"		
15:24:36 75688 INFO	STEP 3: copy data from sour	ce to target	in sub-proc	esses		
15:24:36 75688 INFO	Listing ordinary tables in	"port=54311 l	nost=localho	st dbname=pglo	ader"	
15:24:36 75688 INFO	Fetched information for 56	tables				
	Step	Connection	Duration	Concurrency		
Dump Schema source Oms 1						
	Prepare Schema target Øms 1					
COPY, INDEX, CONSTR	AINTS, VACUUM (wall clock)	both	0ms	4 + 4		
	COPY (cumulative)	both	1s140	4		
	CREATE INDEX (cumulative)	target	0ms	4		
	Finalize Schema	target	0ms	1		
	Total Wall Clock Duration	both	2s143	4 + 4		

And now create the indexes on the target database, using the index definitions from the source database:

\$ pgcopydb copy indexes --resume --not-consistent 15:24:40 75918 INF0 [SOURCE] Copying database from "port=54311 host=localhost dbname=pgloader" 15:24:40 75918 INF0 [TARGET] Copying database into "port=54311 dbname=plop" 15:24:40 75918 INF0 Removing the stale pid file "/tmp/pgcopydb/pgcopydb.pid" 15:24:40 75918 INF0 STEP 4: create indexes in parallel 15:24:40 75918 INF0 Listing ordinary tables in "port=54311 host=localhost dbname=pgloader" 15:24:40 75918 INF0 Fetched information for 56 tables 15:24:40 75930 INF0 Creating 2 indexes for table "csv"."partial"

15:24:40	75922	INFO	Creating 1 index for table	"csv"."track"			
15:24:40	75931	INFO	Creating 1 index for table	"err"."errors	5"		
15:24:40	75928	INFO	Creating 1 index for table	"csv"."blocks	;"		
15:24:40	75925	INFO	Creating 1 index for table	"public"."tra	ck_full"		
15:24:40	76037	INFO	CREATE INDEX IF NOT EXISTS	partial_b_idx	0N csv.part	tial USING bt	ree (b);
15:24:40	76036	INFO	CREATE UNIQUE INDEX IF NOT	EXISTS track_	pkey ON csv.	track USING	<pre>btree (trackid);</pre>
15:24:40	76035	INFO	CREATE UNIQUE INDEX IF NOT	EXISTS partia	l_a_key ON c	csv.partial U	JSING btree (a);
15:24:40	76038	INFO	CREATE UNIQUE INDEX IF NOT	EXISTS errors	_pkey ON err	.errors USIN	WG btree (a);
15:24:40	75987	INFO	Creating 1 index for table	"public"."xze	ero"		
15:24:40	75969	INFO	Creating 1 index for table	"public"."csv	_escape_mode	2"	
15:24:40	75985	INFO	Creating 1 index for table	"public"."udo			
15:24:40	75965	INFO	Creating 1 index for table	"public"."all	.cols"		
15:24:40	75981	INFO	Creating 1 index for table	"public"."ser	rial"		
15:24:40	76039	INFO	CREATE INDEX IF NOT EXISTS	blocks_ip4r_i	dx ON csv.bl	locks USING g	gist (iprange);
15:24:40	76040	INFO	CREATE UNIQUE INDEX IF NOT	EXISTS track	full_pkey ON	V public.trac	<pre>ck_full USING btree (trackid);</pre>
15:24:40	75975	INFO	Creating 1 index for table	"public"."nul	lif"		
15:24:40	76046	INFO	CREATE UNIQUE INDEX IF NOT	EXISTS xzero_	pkey ON publ	lic.xzero USI	ING btree (a);
15:24:40	76048	INFO	CREATE UNIQUE INDEX IF NOT	EXISTS udc_pk	ey ON public	.udc USING b	otree (b);
15:24:40	76047	INFO	CREATE UNIQUE INDEX IF NOT	EXISTS csv_es	cape_mode_pk	cey ON public	c.csv_escape_mode USING btree (id);
15:24:40	76049	INFO	CREATE UNIQUE INDEX IF NOT	EXISTS allcol	.s_pkey ON pu	ublic.allcols	s USING btree (a);
15:24:40	76052	INFO	CREATE UNIQUE INDEX IF NOT	EXISTS nullif	_pkey ON pub	olic."nullif	' USING btree (id);
15:24:40	76050	INFO	CREATE UNIQUE INDEX IF NOT	EXISTS serial	_pkey ON pub	olic.serial U	JSING btree (a);
			Step	Connection	Duration	Concurrency	7
			Dump Schema	source	0ms	1	l
			Prepare Schema	target	0ms	1	L
COPY, II	NDEX,	CONSTR	AINTS, VACUUM (wall clock)	both	0ms	4 + 4	1
			COPY (cumulative)	both	619ms	4	1
			CREATE INDEX (cumulative)	target	1s023	4	Ł
			Finalize Schema	target	0ms	1	L
			Total Wall Clock Duration	both	400ms	4 + 4	- 1
							-

Now re-create the constraints (primary key, unique constraints) from the source database schema into the target database:

\$ pgcopydb copy constraints --resume --not-consistent 15:24:43 76095 INFO [SOURCE] Copying database from "port=54311 host=localhost dbname=pgloader" 15:24:43 76095 INFO [TARGET] Copying database into "port=54311 dbname=plop" 15:24:43 76095 INFO Removing the stale pid file "/tmp/pgcopydb/pgcopydb.pid" 15:24:43 76095 INFO STEP 4: create constraints 15:24:43 76095 INFO Listing ordinary tables in "port=54311 host=localhost dbname=pgloader" 15:24:43 76095 INFO Fetched information for 56 tables 15:24:43 76099 INFO Fetched Information for 56 tables 15:24:43 76099 INFO ALTER TABLE "csv"."track" ADD CONSTRAINT "track_pkey" PRIMARY KEY USING INDEX "track_pkey"; 15:24:43 76107 INFO ALTER TABLE "csv"."partial" ADD CONSTRAINT "partial_a_key" UNIQUE USING INDEX "partial_a_key"; 15:24:43 76102 INFO ALTER TABLE "public"."track_full" ADD CONSTRAINT "track_full_pkey" PRIMARY KEY USING INDEX "track_full_ \hookrightarrow pkey"; 15:24:43 76142 INFO ALTER TABLE "public"."allcols" ADD CONSTRAINT "allcols_pkey" PRIMARY KEY USING INDEX "allcols_pkey"; 15:24:43 76142 INFO ALTER TABLE "public". "serial" ADD CONSTRAINT "serial_pkey" PRIMARY KEY USING INDEX "serial_pkey"; 15:24:43 76161 INFO ALTER TABLE "public". "serial" ADD CONSTRAINT "serial_pkey" PRIMARY KEY USING INDEX "serial_pkey"; 15:24:43 76161 INFO ALTER TABLE "public". "xzero" ADD CONSTRAINT "xzero_pkey" PRIMARY KEY USING INDEX "xzero_pkey"; 15:24:43 76146 INFO ALTER TABLE "public". "csv_escape_mode" ADD CONSTRAINT "csv_escape_mode_pkey" PRIMARY KEY USING INDEX "csv_ →escape_mode_pkey"; 15:24:43 76154 INFO ALTER TABLE "public"."nullif" ADD CONSTRAINT "nullif_pkey" PRIMARY KEY USING INDEX "nullif_pkey"; 15:24:43 76159 INFO ALTER TABLE "public"."udc" ADD CONSTRAINT "udc_pkey" PRIMARY KEY USING INDEX "udc_pkey"; 15:24:43 76108 INFO ALTER TABLE "err"."errors" ADD CONSTRAINT "errors_pkey" PRIMARY KEY USING INDEX "errors_pkey"; Step Connection Duration Concurrency ---------- -----Dump SchemasourceOmsPrepare SchematargetOmsCOPY, INDEX, CONSTRAINTS, VACUUM (wall clock)bothOmsCOPY (cumulative)both605msCREATE INDEX (cumulative)target1s023Finalize SchematargetOms 1 1 0ms 4 + 44 4 1 Total Wall Clock Duration both 415ms 4 + 4 -----

The next step is a VACUUM ANALYZE on each table that's been just filled-in with the data, and for that we can just use the vacuumdb command from Postgres:

\$ vacuumdb --analyze --dbname "\$PGCOPYDB_TARGET_PGURI" --jobs 4 vacuumdb: vacuuming database "plop" Finally we can restore the post-data section of the schema:

```
$ pgcopydb restore post-data --resume --not-consistent
15:24:50 76328 INF0 Removing the stale pid file "/tmp/pgcopydb/pgcopydb.pid"
15:24:50 76328 INF0 Restoring database from "/tmp/pgcopydb"
15:24:50 76328 INF0 Restoring database into "port=54311 dbname=plop"
15:24:50 76328 INF0 Using pg_restore for Postgres "12.9" at "/Applications/Postgres.app/Contents/Versions/12/bin/pg_restore"
15:24:50 76328 INF0 /Applications/Postgres.app/Contents/Versions/12/bin/pg_restore --dbname 'port=54311 dbname=plop' --use-
→list /tmp/pgcopydb/schema/post.list /tmp/pgcopydb/schema/post.dump
```

4.6 pgcopydb dump

pgcopydb dump - Dump database objects from a Postgres instance

This command prefixes the following sub-commands:

```
pgcopydb dump
schema Dump source database schema as custom files in target directory
pre-data Dump source database pre-data schema as custom files in target directory
post-data Dump source database post-data schema as custom files in target directory
roles Dump source database roles as custome file in work directory
```

4.6.1 pgcopydb dump schema

pgcopydb dump schema - Dump source database schema as custom files in target directory

The command pgcopydb dump schema uses pg_dump to export SQL schema definitions from the given source Postgres instance.

```
pgcopydb dump schema: Dump source database schema as custom files in target directory
usage: pgcopydb dump schema --source <URI> --target <dir>
    --source Postgres URI to the source database
--target Directory where to save the dump files
--dir Work directory to use
--snapshot Use snapshot obtained with pg_export_snapshot
```

4.6.2 pgcopydb dump pre-data

pgcopydb dump pre-data - Dump source database pre-data schema as custom files in target directory

The command pgcopydb dump pre-data uses pg_dump to export SQL schema *pre-data* definitions from the given source Postgres instance.

```
pgcopydb dump pre-data: Dump source database pre-data schema as custom files in target directory
usage: pgcopydb dump schema --source <URI> --target <dir>
--source Postgres URI to the source database
--target Directory where to save the dump files
--dir Work directory to use
--snapshot Use snapshot obtained with pg_export_snapshot
```

4.6.3 pgcopydb dump post-data

pgcopydb dump post-data - Dump source database post-data schema as custom files in target directory

The command pgcopydb dump post-data uses pg_dump to export SQL schema *post-data* definitions from the given source Postgres instance.

```
pgcopydb dump post-data: Dump source database post-data schema as custom files in target directory
usage: pgcopydb dump schema --source <URI> --target <dir>
--source Postgres URI to the source database
--target Directory where to save the dump files
--dir Work directory to use
--snapshot Use snapshot obtained with pg_export_snapshot
```

4.6.4 pgcopydb dump roles

pgcopydb dump roles - Dump source database roles as custome file in work directory

The command pgcopydb dump roles uses pg_dumpall –roles-only to export SQL definitions of the roles found on the source Postgres instance.

```
pgcopydb dump roles: Dump source database roles as custome file in work directory
usage: pgcopydb dump roles --source <URI>
--source Postgres URI to the source database
--target Directory where to save the dump files
--dir Work directory to use
```

The pg_dumpall --roles-only is used to fetch the list of roles from the source database, and this command includes support for passwords. As a result, this operation requires the superuser privileges.

4.6.5 Description

The pgcopydb dump schema command implements the first step of the full database migration and fetches the schema definitions from the source database.

When the command runs, it calls pg_dump to get first the pre-data schema output in a Postgres custom file, and then again to get the post-data schema output in another Postgres custom file.

The output files are written to the schema sub-directory of the --target directory.

The pgcopydb dump pre-data and pgcopydb dump post-data are limiting their action to respectively the predata and the post-data sections of the pg_dump.

4.6.6 Options

The following options are available to pgcopydb dump schema:

source	Connection string to the source Postgres instance. See the Postgres documentation for connection strings for the details. In short both the quoted form "host= dbname=" and the URI form postgres://user@host:5432/dbname are supported.
target	Connection string to the target Postgres instance.
dir	During its normal operations pgcopydb creates a lot of temporary files to track sub-processes progress. Temporary files are created in the directory location given by this option, or defaults to \${TMPDIR}/pgcopydb when the environment variable is set, or then to /tmp/pgcopydb.

snapshot	Instead of exporting its own snapshot by calling the PostgreSQL function pg_export_snapshot() it is possible for pgcopydb to re-use an already exported snapshot.
verbose	Increase current verbosity. The default level of verbosity is INFO. In ascending order pgcopydb knows about the following verbosity levels: FATAL, ERROR, WARN, INFO, NOTICE, DEBUG, TRACE.
debug	Set current verbosity to DEBUG level.
trace	Set current verbosity to TRACE level.
quiet	Set current verbosity to ERROR level.

4.6.7 Environment

PGCOPYDB_SOURCE_PGURI

Connection string to the source Postgres instance. When **--source** is ommitted from the command line, then this environment variable is used.

4.6.8 Examples

First, using pgcopydb dump schema

```
$ pgcopydb dump schema --source "port=5501 dbname=demo" --target /tmp/target
09:35:21 3926 INF0 Dumping database from "port=5501 dbname=demo"
09:35:21 3926 INF0 Dumping database into directory "/tmp/target"
09:35:21 3926 INF0 Found a stale pidfile at "/tmp/target/pgcopydb.pid"
09:35:21 3926 WARN Removing the stale pid file "/tmp/target/pgcopydb.pid"
09:35:21 3926 INF0 Using pg_dump for Postgres "12.9" at "/Applications/Postgres.app/Contents/Versions/12/bin/pg_dump"
09:35:21 3926 INF0 Using pg_dump for Postgres.app/Contents/Versions/12/bin/pg_dump -Fc --section pre-data --file /tmp/target/
--schema/pre.dump 'port=5501 dbname=demo'
09:35:22 3926 INF0 /Applications/Postgres.app/Contents/Versions/12/bin/pg_dump -Fc --section post-data --file /tmp/target/
--schema/post.dump 'port=5501 dbname=demo'
```

Once the previous command is finished, the pg_dump output files can be found in /tmp/target/schema and are named pre.dump and post.dump. Other files and directories have been created.

\$ find /tmp/target /tmp/target /tmp/target/pgcopydb.pid /tmp/target/schema /tmp/target/schema/post.dump /tmp/target/schema/pre.dump /tmp/target/run /tmp/target/run/tables /tmp/target/run/indexes

Then we have almost the same thing when using the other forms.

We can see that pgcopydb dump pre-data only does the pre-data section of the dump.

\$ pgcopydb dump pre-data --source "port=5501 dbname=demo" --target /tmp/target 09:35:21 3926 INF0 Dumping database from "port=5501 dbname=demo" 09:35:21 3926 INF0 Dumping database into directory "/tmp/target" 09:35:21 3926 INF0 Found a stale pidfile at "/tmp/target/pgcopydb.pid" 09:35:21 3926 INF0 Kenoving the stale pid file "/tmp/target/pgcopydb.pid" 09:35:21 3926 INF0 Using pg_dump for Postgres "12.9" at "/Applications/Postgres.app/Contents/Versions/12/bin/pg_dump" 09:35:21 3926 INF0 /Applications/Postgres.app/Contents/Versions/12/bin/pg_dump 'port=5501 dbname=demo'

And then pgcopydb dump post-data only does the post-data section of the dump.

4.7 pgcopydb restore

pgcopydb restore - Restore database objects into a Postgres instance

This command prefixes the following sub-commands:

```
pgcopydb restore
schema Restore a database schema from custom files to target database
pre-data Restore a database pre-data schema from custom file to target database
post-data Restore a database post-data schema from custom file to target database
roles Restore database roles from SQL file to target database
parse-list Parse pg_restore --list output from custom file
```

4.7.1 pgcopydb restore schema

pgcopydb restore schema - Restore a database schema from custom files to target database

The command pgcopydb restore schema uses pg_restore to create the SQL schema definitions from the given pgcopydb dump schema export directory. This command is not compatible with using Postgres files directly, it must be fed with the directory output from the pgcopydb dump ... commands.

```
pgcopydb restore schema: Restore a database schema from custom files to target database
usage: pgcopydb restore schema --dir <dir> [ --source <URI> ] --target <URI>
  --source
                       Postgres URI to the source database
                       Postgres URI to the target database
  --target
  --dir
                       Work directory to use
  --drop-if-exists
                       On the target database, clean-up from a previous run first
                      Do not set ownership of objects to match the original database
  --no-owner
  --no-acl
                      Prevent restoration of access privileges (grant/revoke commands).
                      Do not output commands to restore comments
  --no-comments
  --filters <filename> Use the filters defined in <filename>
                      Allow restarting when temp files exist already
  --restart
  --resume
                       Allow resuming operations after a failure
  --not-consistent
                       Allow taking a new snapshot on the source database
```

4.7.2 pgcopydb restore pre-data

pgcopydb restore pre-data - Restore a database pre-data schema from custom file to target database

The command pgcopydb restore pre-data uses pg_restore to create the SQL schema definitions from the given pgcopydb dump schema export directory. This command is not compatible with using Postgres files directly, it must be fed with the directory output from the pgcopydb dump ... commands.

```
pgcopydb restore pre-data: Restore a database pre-data schema from custom file to target database
usage: pgcopydb restore pre-data --dir <dir> [ --source <URI> ] --target <URI>
--source Postgres URI to the source database
--target Postgres URI to the target database
--dir Work directory to use
--drop-if-exists On the target database, clean-up from a previous run first
--no-owner Do not set ownership of objects to match the original database
--no-acl Prevent restoration of access privileges (grant/revoke commands).
```

no-comments	Do not output commands to restore comments
filters <filename></filename>	Use the filters defined in <filename></filename>
restart	Allow restarting when temp files exist already
resume	Allow resuming operations after a failure
not -consistent	Allow taking a new snapshot on the source database

4.7.3 pgcopydb restore post-data

pgcopydb restore post-data - Restore a database post-data schema from custom file to target database

The command pgcopydb restore post-data uses pg_restore to create the SQL schema definitions from the given pgcopydb dump schema export directory. This command is not compatible with using Postgres files directly, it must be fed with the directory output from the pgcopydb dump ... commands.

```
pgcopydb restore post-data: Restore a database post-data schema from custom file to target database
Postgres URI to the source database
  --source
                    Postgres URI to the target database
 --target
 --dir
                    Work directory to use
                    Do not set ownership of objects to match the original database
 --no-owner
                    Prevent restoration of access privileges (grant/revoke commands)
 --no-acl
 --no-comments
                    Do not output commands to restore comments
 --filters <filename> Use the filters defined in <filename>
                    Allow restarting when temp files exist already
 --restart
                    Allow resuming operations after a failure
  --resume
  --not-consistent
                    Allow taking a new snapshot on the source database
```

4.7.4 pgcopydb restore roles

pgcopydb restore roles - Restore database roles from SQL file to target database

The command pgcopydb restore roles runs the commands from the SQL script obtained from the command pgcopydb dump roles. Roles that already exist on the target database are skipped.

The pg_dumpall command issues two lines per role, the first one is a CREATE ROLE SQL command, the second one is an ALTER ROLE SQL command. Both those lines are skipped when the role already exists on the target database.

```
pgcopydb restore roles: Restore database roles from SQL file to target database
usage: pgcopydb restore roles --dir <dir> [ --source <URI> ] --target <URI>
--source Postgres URI to the source database
--target Postgres URI to the target database
--dir Work directory to use
```

4.7.5 pgcopydb restore parse-list

pgcopydb restore parse-list - Parse pg_restore -list output from custom file

The command pgcopydb restore parse-list outputs pg_restore to list the archive catalog of the custom file format file that has been exported for the post-data section.

When using the --filters option, then the source database connection is used to grab all the dependend objects that should also be filtered, and the output of the command shows those pg_restore catalog entries commented out.

A pg_restore archive catalog entry is commented out when its line starts with a semi-colon character (;).

```
pgcopydb restore parse-list: Parse pg_restore --list output from custom file
usage: pgcopydb restore parse-list --dir <dir> [ --source <URI> ] --target <URI>
--source Postgres URI to the source database
```

target	Postgres URI to the target database
dir	Work directory to use
filters <filename></filename>	Use the filters defined in <filename></filename>
skip-extensions	Skip restoring extensions
restart	Allow restarting when temp files exist already
resume	Allow resuming operations after a failure
not -consistent	Allow taking a new snapshot on the source database

4.7.6 Description

The pgcopydb restore schema command implements the creation of SQL objects in the target database, second and last steps of a full database migration.

When the command runs, it calls pg_restore on the files found at the expected location within the --target directory, which has typically been created with the pgcopydb dump schema command.

The pgcopydb restore pre-data and pgcopydb restore post-data are limiting their action to respectively the pre-data and the post-data files in the source directory.

4.7.7 Options

The following options are available to pgcopydb restore schema:

source	Connection string to the source Postgres instance. See the Postgres documentation for connection strings for the details. In short both the quoted form "host= dbname=" and the URI form postgres://user@host:5432/dbname are supported.
target	Connection string to the target Postgres instance.
dir	During its normal operations pgcopydb creates a lot of temporary files to track sub-processes progress. Temporary files are created in the directory location given by this option, or defaults to \${TMPDIR}/pgcopydb when the environment variable is set, or then to /tmp/pgcopydb.
drop-if-exists	When restoring the schema on the target Postgres instance, pgcopydb actually uses pg_restore. When this options is specified, then the following pg_restore options are also used:cleanif-exists.
	This option is useful when the same command is run several times in a row, either to fix a previous mistake or for instance when used in a continuous integration system.
	This option causes DROP TABLE and DROP INDEX and other DROP commands to be used. Make sure you understand what you're doing here!
no-owner	Do not output commands to set ownership of objects to match the original database. By default, pg_restore issues ALTER OWNER or SET SESSION AUTHORIZATION statements to set ownership of created schema elements. These statements will fail unless the initial connection to the database is made by a superuser (or the same user that owns all of the objects in the script). Withno-owner, any user name can be used for the initial connection, and this user will own all the created objects.
filters <filename></filename>	This option allows to exclude table and indexes from the copy operations. See <i>Filtering</i> for details about the expected file format and the filtering options available.

skip-extensions	Skip copying extensions from the source database to the target database.
	When used, schema that extensions depend-on are also skipped: it is expected that creating needed extensions on the target system is then the responsibility of an- other command (such as <i>pgcopydb copy extensions</i>), and schemas that extensions depend-on are part of that responsibility.
	Because creating extensions require superuser, this allows a multi-steps approach where extensions are dealt with superuser privileges, and then the rest of the pg- copydb operations are done without superuser privileges.
restart	When running the pgcopydb command again, if the work directory already con- tains information from a previous run, then the command refuses to proceed and delete information that might be used for diagnostics and forensics.
	In that case, therestart option can be used to allow pgcopydb to delete traces from a previous run.
resume	When the pgcopydb command was terminated before completion, either by an interrupt signal (such as C-c or SIGTERM) or because it crashed, it is possible to resume the database migration.
	When resuming activity from a previous run, table data that was fully copied over to the target server is not sent again. Table data that was interrupted during the COPY has to be started from scratch even when usingresume: the COPY command in Postgres is transactional and was rolled back.
	Same reasonning applies to the CREATE INDEX commands and ALTER TABLE commands that pgcopydb issues, those commands are skipped on aresume run only if known to have run through to completion on the previous one.
	Finally, usingresume requires the use ofnot-consistent.
not-consistent	In order to be consistent, pgcopydb exports a Postgres snapshot by calling the pg_export_snapshot() function on the source database server. The snapshot is then re-used in all the connections to the source database server by using the SET TRANSACTION SNAPSHOT command.
	Per the Postgres documentation about pg_export_snapshot:
	Saves the transaction's current snapshot and returns a text string iden- tifying the snapshot. This string must be passed (outside the database) to clients that want to import the snapshot. The snapshot is available for import only until the end of the transaction that exported it.
	Now, when the pgcopydb process was interrupted (or crashed) on a previous run, it is possible to resume operations, but the snapshot that was exported does not exists anymore. The pgcopydb command can only resume operations with a new snapshot, and thus can not ensure consistency of the whole data set, because each run is now using their own snapshot.
snapshot	Instead of exporting its own snapshot by calling the PostgreSQL function pg_export_snapshot() it is possible for pgcopydb to re-use an already exported snapshot.
verbose	Increase current verbosity. The default level of verbosity is INFO. In ascending order pgcopydb knows about the following verbosity levels: FATAL, ERROR, WARN, INFO, NOTICE, DEBUG, TRACE.
debug	Set current verbosity to DEBUG level.
trace	Set current verbosity to TRACE level.

--quiet

Set current verbosity to ERROR level.

4.7.8 Environment

PGCOPYDB_TARGET_PGURI

Connection string to the target Postgres instance. When --target is ommitted from the command line, then this environment variable is used.

PGCOPYDB_DROP_IF_EXISTS

When true (or *yes*, or *on*, or 1, same input as a Postgres boolean) then pgcopydb uses the pg_restore options --clean --if-exists when creating the schema on the target Postgres instance.

4.7.9 Examples

First, using pgcopydb restore schema

```
$ PGCOPYDB_DROP_IF_EXISTS=on pgcopydb restore schema --source /tmp/target/ --target "port=54314 dbname=demo"
09:54:37 20401 INF0 Restoring database from "/tmp/target/"
09:54:37 20401 INF0 Restoring database into "port=54314 dbname=demo"
09:54:37 20401 INF0 Found a stale pidfile at "/tmp/target//pgcopydb.pid"
09:54:37 20401 INF0 Found a stale pid file "/tmp/target//pgcopydb.pid"
09:54:37 20401 INF0 Using pg_restore for Postgres "12.9" at "/Applications/Postgres.app/Contents/Versions/12/bin/pg_restore"
09:54:37 20401 INF0 /Applications/Postgres.app/Contents/Versions/12/bin/pg_restore --dbname 'port=54314 dbname=demo' --clean_
---if-exists /tmp/target//schema/post.list /tmp/target//schema/post.dump
```

Then the pgcopydb restore pre-data and pgcopydb restore post-data would look the same with just a single call to pg_restore instead of the both of them.

Using pgcopydb restore parse-list it's possible to review the filtering options and see how pg_restore catalog entries are being commented-out.

```
$ cat ./tests/filtering/include.ini
Finclude-only-table]
public.actor
public.categorv
public.film
public.film_actor
public.film_category
public.language
public.rental
[exclude-index]
public.idx_store_id_film_id
[exclude-table-data]
public.rental
$ pgcopydb restore parse-list --dir /tmp/pagila/pgcopydb --resume --not-consistent --filters ./tests/filtering/include.ini
11:41:22 75175 INFO Running pgcopydb version 0.5.8.ge0d2038 from "/Users/dim/dev/PostgreSQL/pgcopydb/./src/bin/pgcopydb/
  →pgcopydb"
11:41:22 75175 INFO
                       [SOURCE] Restoring database from "postgres://@:54311/pagila?"
11:41:22 75175 INFO
                       [TARGET] Restoring database into "postgres://@:54311/plop?"
11:41:22 75175 INFO Using work dir "/tmp/pagila/pgcopydb"
11:41:22 75175 INFO Removing the stale pid file "/tmp/pagila/pgcopydb/pgcopydb.pid"
11:41:22 75175 INFO Work directory "/tmp/pagila/pgcopydb" already exists
11:41:22 75175 INFO Schema dump for pre-data and post-data section have been done
11:41:22 75175 INFO Restoring database from existing files at "/tmp/pagila/pgcopydb"
11:41:22 75175 INFO Using pg_restore for Postgres "12.9" at "/Applications/Postgres.app/Contents/Versions/12/bin/pg_restore"
11:41:22 75175 INFO Exported snapshot "00000003-0003209A-1" from the source database
3242; 2606 317973 CONSTRAINT public actor actor_pkey postgres
;3258; 2606 317975 CONSTRAINT public address address_pkey postgres
3245; 2606 317977 CONSTRAINT public category category_pkey postgres
;3261; 2606 317979 CONSTRAINT public city city_pkey postgres
;3264; 2606 317981 CONSTRAINT public country country_pkey postgres
```

:3237: 2606 317983 CONSTRAINT public customer customer_pkey postgres 3253; 2606 317985 CONSTRAINT public film_actor film_actor_pkey postgres 3256; 2606 317987 CONSTRAINT public film_category film_category_pkey postgres 3248; 2606 317989 CONSTRAINT public film film_pkey postgres ;3267; 2606 317991 CONSTRAINT public inventory inventory_pkey postgres 3269; 2606 317993 CONSTRAINT public language language_pkey postgres 3293; 2606 317995 CONSTRAINT public rental rental_pkey postgres ;3295; 2606 317997 CONSTRAINT public staff staff_pkey postgres ;3298; 2606 317999 CONSTRAINT public store store_pkey postgres 3246; 1259 318000 INDEX public film_fulltext_idx postgres 3243; 1259 318001 INDEX public idx_actor_last_name postgres ;3238; 1259 318002 INDEX public idx_fk_address_id postgres ;3259; 1259 318003 INDEX public idx_fk_city_id postgres ;3262; 1259 318004 INDEX public idx_fk_country_id postgres ;3270; 1259 318005 INDEX public idx_fk_customer_id postgres 3254; 1259 318006 INDEX public idx_fk_film_id postgres 3290; 1259 318007 INDEX public idx_fk_inventory_id postgres 3249; 1259 318008 INDEX public idx_fk_language_id postgres 3250; 1259 318009 INDEX public idx_fk_original_language_id postgres ;3272; 1259 318010 INDEX public idx_fk_payment_p2020_01_customer_id postgres ;3271; 1259 318011 INDEX public idx_fk_staff_id postgres ;3273; 1259 318012 INDEX public idx_fk_payment_p2020_01_staff_id postgres ;3275; 1259 318013 INDEX public idx_fk_payment_p2020_02_customer_id postgres ;3276; 1259 318014 INDEX public idx_fk_payment_p2020_02_staff_id postgres ;3278; 1259 318015 INDEX public idx_fk_payment_p2020_03_customer_id postgres ;3279; 1259 318016 INDEX public idx_fk_payment_p2020_03_staff_id postgres ;3281; 1259 318017 INDEX public idx_fk_payment_p2020_04_customer_id postgres ;3282; 1259 318018 INDEX public idx_fk_payment_p2020_04_staff_id postgres ;3284; 1259 318019 INDEX public idx_fk_payment_p2020_05_customer_id postgres ;3285; 1259 318020 INDEX public idx_fk_payment_p2020_05_staff_id postgres ;3287; 1259 318021 INDEX public idx_fk_payment_p2020_06_customer_id postgres ;3288; 1259 318022 INDEX public idx_fk_payment_p2020_06_staff_id postgres ;3239; 1259 318023 INDEX public idx_fk_store_id postgres ;3240; 1259 318024 INDEX public idx_last_name postgres ;3265; 1259 318025 INDEX public idx_store_id_film_id postgres 3251; 1259 318026 INDEX public idx_title postgres ;3296; 1259 318027 INDEX public idx_unq_manager_staff_id postgres 3291; 1259 318028 INDEX public idx_unq_rental_rental_date_inventory_id_customer_id postgres ;3274; 1259 318029 INDEX public payment_p2020_01_customer_id_idx postgres ;3277; 1259 318030 INDEX public payment_p2020_02_customer_id_idx postgres ;3280; 1259 318031 INDEX public payment_p2020_03_customer_id_idx postgres ;3283; 1259 318032 INDEX public payment_p2020_04_customer_id_idx postgres ;3286; 1259 318033 INDEX public payment_p2020_05_customer_id_idx postgres ;3289; 1259 318034 INDEX public payment_p2020_06_customer_id_idx postgres ;3299; 0 0 INDEX ATTACH public idx_fk_payment_p2020_01_staff_id postgres ;3301; 0 0 INDEX ATTACH public idx_fk_payment_p2020_02_staff_id postgres ;3303; 0 0 INDEX ATTACH public idx_fk_payment_p2020_03_staff_id postgres ;3305; 0 0 INDEX ATTACH public idx_fk_payment_p2020_04_staff_id postgres ;3307; 0 0 INDEX ATTACH public idx_fk_payment_p2020_05_staff_id postgres ;3309; 0 0 INDEX ATTACH public idx_fk_payment_p2020_06_staff_id postgres ;3300; 0 0 INDEX ATTACH public payment_p2020_01_customer_id_idx postgres ;3302; 0 0 INDEX ATTACH public payment_p2020_02_customer_id_idx postgres ;3304; 0 0 INDEX ATTACH public payment_p2020_03_customer_id_idx postgres ;3306; 0 0 INDEX ATTACH public payment_p2020_04_customer_id_idx postgres ;3308; 0 0 INDEX ATTACH public payment_p2020_05_customer_id_idx postgres ;3310; 0 0 INDEX ATTACH public payment_p2020_06_customer_id_idx postgres 3350; 2620 318035 TRIGGER public film film_fulltext_trigger postgres 3348; 2620 318036 TRIGGER public actor last_updated postgres ;3354; 2620 318037 TRIGGER public address last_updated postgres 3349; 2620 318038 TRIGGER public category last_updated postgres ;3355; 2620 318039 TRIGGER public city last_updated postgres ;3356; 2620 318040 TRIGGER public country last_updated postgres ;3347; 2620 318041 TRIGGER public customer last_updated postgres 3351; 2620 318042 TRIGGER public film last_updated postgres 3352; 2620 318043 TRIGGER public film_actor last_updated postgres 3353; 2620 318044 TRIGGER public film_category last_updated postgres ;3357; 2620 318045 TRIGGER public inventory last_updated postgres 3358; 2620 318046 TRIGGER public language last_updated postgres 3359; 2620 318047 TRIGGER public rental last_updated postgres ;3360; 2620 318048 TRIGGER public staff last_updated postgres ;3361; 2620 318049 TRIGGER public store last_updated postgres ;3319; 2606 318050 FK CONSTRAINT public address address_city_id_fkey postgres ;3320; 2606 318055 FK CONSTRAINT public city city_country_id_fkey postgres ;3311; 2606 318060 FK CONSTRAINT public customer customer_address_id_fkey postgres ;3312; 2606 318065 FK CONSTRAINT public customer customer_store_id_fkey postgres 3315; 2606 318070 FK CONSTRAINT public film_actor film_actor_actor_id_fkey postgres 3316; 2606 318075 FK CONSTRAINT public film_actor film_actor_film_id_fkey postgres 3317; 2606 318080 FK CONSTRAINT public film_category film_category_category_id_fkey postgres

3318; 2	606	318085 FK	CONSTRAINT	<pre>public film_category film_category_film_id_fkey postgres</pre>
3313; 2	606	318090 FK	CONSTRAINT	<pre>public film film_language_id_fkey postgres</pre>
3314; 2	606	318095 FK	CONSTRAINT	<pre>public film film_original_language_id_fkey postgres</pre>
;3321;	2606	318100 F	K CONSTRAINT	f public inventory inventory_film_id_fkey postgres
;3322;	2606	318105 F	K CONSTRAINT	f public inventory inventory_store_id_fkey postgres
;3323;	2606	318110 F	K CONSTRAINT	f public payment_p2020_01 payment_p2020_01_customer_id_fkey postgres
;3324;	2606	318115 F	K CONSTRAINT	f public payment_p2020_01 payment_p2020_01_rental_id_fkey postgres
;3325;	2606	318120 F	K CONSTRAINT	f public payment_p2020_01 payment_p2020_01_staff_id_fkey postgres
;3326;	2606	318125 F	K CONSTRAINT	f public payment_p2020_02 payment_p2020_02_customer_id_fkey postgres
;3327;	2606	318130 F	K CONSTRAINT	f public payment_p2020_02 payment_p2020_02_rental_id_fkey postgres
;3328;	2606	318135 F	K CONSTRAINT	f public payment_p2020_02 payment_p2020_02_staff_id_fkey postgres
;3329;	2606	318140 F	K CONSTRAINT	f public payment_p2020_03 payment_p2020_03_customer_id_fkey postgres
;3330;	2606	318145 F	K CONSTRAINT	f public payment_p2020_03 payment_p2020_03_rental_id_fkey postgres
;3331;	2606	318150 F	K CONSTRAINT	f public payment_p2020_03 payment_p2020_03_staff_id_fkey postgres
;3332;	2606	318155 F	K CONSTRAINT	f public payment_p2020_04 payment_p2020_04_customer_id_fkey postgres
;3333;	2606	318160 F	K CONSTRAINT	f public payment_p2020_04 payment_p2020_04_rental_id_fkey postgres
;3334;	2606	318165 F	K CONSTRAINT	f public payment_p2020_04 payment_p2020_04_staff_id_fkey postgres
;3335;	2606	318170 F	K CONSTRAINT	f public payment_p2020_05 payment_p2020_05_customer_id_fkey postgres
;3336;	2606	318175 F	K CONSTRAINT	f public payment_p2020_05 payment_p2020_05_rental_id_fkey postgres
;3337;	2606	318180 F	K CONSTRAINT	f public payment_p2020_05 payment_p2020_05_staff_id_fkey postgres
;3338;	2606	318185 F	K CONSTRAINT	f public payment_p2020_06 payment_p2020_06_customer_id_fkey postgres
;3339;	2606	318190 F	K CONSTRAINT	f public payment_p2020_06 payment_p2020_06_rental_id_fkey postgres
;3340;	2606	318195 F	K CONSTRAINT	f public payment_p2020_06 payment_p2020_06_staff_id_fkey postgres
;3341;	2606	318200 F	K CONSTRAINT	f public rental rental_customer_id_fkey postgres
;3342;	2606	318205 F	K CONSTRAINT	f public rental rental_inventory_id_fkey postgres
;3343;	2606	318210 F	K CONSTRAINT	<pre>public rental rental_staff_id_fkey postgres</pre>
;3344;	2606	318215 F	K CONSTRAINT	<pre>public staff_address_id_fkey postgres</pre>
;3345;	2606	318220 F	K CONSTRAINT	<pre>public staff staff_store_id_fkey postgres</pre>
;3346;	2606	318225 F	K CONSTRAINT	<pre>F public store store_address_id_fkey postgres</pre>

4.8 pgcopydb list

pgcopydb list - List database objects from a Postgres instance

This command prefixes the following sub-commands:

```
pgcopydb list
 extensions
               List all the source extensions to copy
               List all the source tables to copy data from
  tables
  table-parts List a source table copy partitions
               List all the source sequences to copy data \ensuremath{\textit{from}}
  sequences
  indexes
               List all the indexes to create again after copying the data
  depends
               List all the dependencies to filter-out
               List the schema to migrate, formatted in JSON
  schema
 progress
               List the progress
```

4.8.1 pgcopydb list extensions

pgcopydb list extensions - List all the source extensions to copy

The command pgcopydb list extensions connects to the source database and executes a SQL query using the Postgres catalogs to get a list of all the extensions to COPY to the target database.

```
pgcopydb list extensions: List all the source extensions to copy
usage: pgcopydb list extensions --source ...
--source Postgres URI to the source database
```

4.8.2 pgcopydb list tables

pgcopydb list tables - List all the source tables to copy data from

The command pgcopydb list tables connects to the source database and executes a SQL query using the Postgres catalogs to get a list of all the tables to COPY the data from.

```
pgcopydb list tables: List all the source tables to copy data from
usage: pgcopydb list tables --source ...
--source Postgres URI to the source database
--filter <filename> Use the filters defined in <filename>
--list-skipped List only tables that are setup to be skipped
--without-pkey List only tables that have no primary key
```

4.8.3 pgcopydb list table-parts

pgcopydb list table-parts - List a source table copy partitions

The command pgcopydb list table-parts connects to the source database and executes a SQL query using the Postgres catalogs to get detailed information about the given source table, and then another SQL query to compute how to split this source table given the size threshold argument.

```
pgcopydb list table-parts: List a source table copy partitions
usage: pgcopydb list table-parts --source ...
--source Postgres URI to the source database
--schema-name Name of the schema where to find the table
--table-name Name of the target table
--split-tables-larger-than Size threshold to consider partitioning
```

4.8.4 pgcopydb list sequences

pgcopydb list sequences - List all the source sequences to copy data from

The command pgcopydb list sequences connects to the source database and executes a SQL query using the Postgres catalogs to get a list of all the sequences to COPY the data from.

```
pgcopydb list sequences: List all the source sequences to copy data from
usage: pgcopydb list sequences --source ...
--source Postgres URI to the source database
--filter <filename> Use the filters defined in <filename>
--list-skipped List only tables that are setup to be skipped
```

4.8.5 pgcopydb list indexes

pgcopydb list indexes - List all the indexes to create again after copying the data

The command pgcopydb list indexes connects to the source database and executes a SQL query using the Postgres catalogs to get a list of all the indexes to COPY the data from.

```
pgcopydb list indexes: List all the indexes to create again after copying the data
usage: pgcopydb list indexes --source ... [ --schema-name [ --table-name ] ]

--source Postgres URI to the source database

--schema-name Name of the schema where to find the table

--table-name Name of the target table

--filter <filename> Use the filters defined in <filename>

--list-skipped List only tables that are setup to be skipped
```

4.8.6 pgcopydb list depends

pgcopydb list depends - List all the dependencies to filter-out

The command pgcopydb list depends connects to the source database and executes a SQL query using the Postgres catalogs to get a list of all the objects that depend on excluded objects from the filtering rules.

```
pgcopydb list depends: List all the dependencies to filter-out
usage: pgcopydb list depends --source ... [ --schema-name [ --table-name ] ]
--source Postgres URI to the source database
--schema-name Name of the schema where to find the table
--table-name Name of the target table
--filter <filename> Use the filters defined in <filename>
--list-skipped List only tables that are setup to be skipped
```

4.8.7 pgcopydb list schema

pgcopydb list schema - List the schema to migrate, formatted in JSON

The command pgcopydb list schema connects to the source database and executes a SQL queries using the Postgres catalogs to get a list of the tables, indexes, and sequences to migrate. The command then outputs a JSON formatted string that contains detailed information about all those objects.

```
pgcopydb list schema: List the schema to migrate, formatted in JSON
usage: pgcopydb list schema --source ...
--source Postgres URI to the source database
--filter <filename> Use the filters defined in <filename>
```

4.8.8 pgcopydb list progress

pgcopydb list progress - List the progress

The command pgcopydb list progress reads the schema.json file in the work directory, parses it, and then computes how many tables and indexes are planned to be copied and created on the target database, how many have been done already, and how many are in-progress.

When using the option --json the JSON formatted output also includes a list of all the tables and indexes that are currently being processed.

```
pgcopydb list progress: List the progress
usage: pgcopydb list progress --source ...
--source Postgres URI to the source database
--json Format the output using JSON
```

4.8.9 Options

The following options are available to pgcopydb dump schema:

source	Connection string to the source Postgres instance. See the Postgres documentation for connection strings for the details. In short both the quoted form "host= dbname=" and the URI form postgres://user@host:5432/dbname are supported.			
schema-name	Filter indexes from a given schema only.			
table-name	Filter indexes from a given table only (useschema-name to fully qualify the table).			

without-pkey	List only tables from the source database when they have no primary key attached to their schema.
filter <filename></filename>	This option allows to skip objects in the list operations. See <i>Filtering</i> for details about the expected file format and the filtering options available.
list-skipped	Instead of listing objects that are selected for copy by the filters installed with thefilter option, list the objects that are going to be skipped when using the filters.
json	The output of the command is formatted in JSON, when supported. Ignored otherwise.
verbose	Increase current verbosity. The default level of verbosity is INFO. In ascending order pgcopydb knows about the following verbosity levels: FATAL, ERROR, WARN, INFO, NOTICE, DEBUG, TRACE.
debug	Set current verbosity to DEBUG level.
trace	Set current verbosity to TRACE level.
quiet	Set current verbosity to ERROR level.

4.8.10 Environment

PGCOPYDB_SOURCE_PGURI

Connection string to the source Postgres instance. When --source is ommitted from the command line, then this environment variable is used.

4.8.11 Examples

Listing the tables:

```
$ pgcopydb list tables
14:35:18 13827 INFO Listing ordinary tables in "port=54311 host=localhost dbname=pgloader"
14:35:19 13827 INFO Fetched information for 56 tables
                                                                               On-disk size
    OID |
                    Schema Name |
                                            Table Name | Est. Row Count |
  17085
                            csv
                                                 track
                                                                     3503
                                                                                     544 kB
   17098
                       expected
                                                 track
                                                                     3503
                                                                                     544 kB
   17290
                       expected |
                                            track_full |
                                                                     3503
                                                                                     544 kB
   17276
                        public |
                                            track_full
                                                                     3503
                                                                                     544 kB
   17016
                       expected
                                             districts
                                                                      440
                                                                                      72 kB
   17007
                         public
                                             districts
                                                                      440
                                                                                      72 kB
  16998
                            csv
                                                blocks
                                                                      460
                                                                                      48 kB
   17003
                       expected
                                                blocks
                                                                      460
                                                                                      48 kB
  17405
                                               partial
                                                                                      16 kB
                            csv
                                                                       7
   17323
                            err
                                                errors
                                                                       0
                                                                                      16 kB
  16396
                       expected
                                               allcols
                                                                       0
                                                                                      16 kB
  17265
                                                                       0
                                                                                      16 kB
                       expected
                                                   csv
  17056
                                       csv_escape_mode
                                                                        0 |
                                                                                      16 kB
                       expected
  17331
                                                                        0 |
                                                                                      16 kB
                       expected
                                                errors
  17116
                                                                        0 |
                                                                                      16 kB
                       expected
                                                 group
  17134
                                                                                      16 kB
                       expected |
                                                                       0 |
                                                  json
  17074
                                              matching
                       expected
                                                                        0 |
                                                                                      16 kB
  17201
                                                                        0 |
                       expected
                                                nullif
                                                                                      16 kB
  17229
                       expected
                                                 nulls
                                                                        0 |
                                                                                      16 kB
  17417
                                                                       0 |
                                                                                      16 kB
                                               partial
                       expected
  17313
                       expected
                                               reg2013
                                                                        0 |
                                                                                      16 kB
  17437
                                                                        0 |
                                                                                      16 kB
                       expected
                                                serial
  17247
                                                                       0 |
                                                                                      16 kB
                       expected
                                                  sexp
  17378
                                                                       0
                                                                                      16 kB
                       expected |
                                                 test1
                                                                                      16 kB
  17454
                       expected |
                                                   udc
                                                                        0 |
                                                                                      16 kB
   17471
                       expected |
                                                 xzero
                                                                        0 |
  17372 |
                                                                        0 |
                                                                                      16 kB
                         nsitra |
                                                 test1
```

16388	public	allcols	0		16 kB	
17256	public	CSV	0		16 kB	
17047	public	<pre>csv_escape_mode</pre>	0		16 kB	
17107	public	group	0		16 kB	
17125	public	json	0		16 kB	
17065	public	matching	0		16 kB	
17192	public	nullif	0		16 kB	
17219	public	nulls	0		16 kB	
17307	public	reg2013	0		16 kB	
17428	public	serial	0		16 kB	
17238	public	sexp	0		16 kB	
17446	public	udc	0		16 kB	
17463	public	xzero	0		16 kB	
17303	expected	copyhex	0	8192	bytes	
17033	expected	dateformat	0	8192	bytes	
17366	expected	fixed	0	8192	bytes	
17041	expected	jordane	0	8192	bytes	
17173	expected	missingcol	0	8192	bytes	
17396	expected	overflow	0	8192	bytes	
17186	expected	tab_csv	0	8192	bytes	
17213	expected	temp	0	8192	bytes	
17299	public	copyhex	0	8192	bytes	
17029	public	dateformat	0	8192	bytes	
17362	public	fixed	0	8192	bytes	
17037	public	jordane	0	8192	bytes	
17164	public	missingcol	0	8192	bytes	
17387	public	overflow	0	8192	bytes	
17182	public	tab_csv	0	8192	bytes	
17210	public	temp	0	8192	bytes	

Listing a table list of COPY partitions:

\$ pgcopydb list table-parts --table-name rental --split-at 300kB 16:43:26 73794 INFO Running pgcopydb version 0.8.8.g0838291.dirty from "/Users/dim/dev/PostgreSQL/pgcopydb/src/bin/pgcopydb/ lb:45:20 /3/94 INFO Running Fyce, ...
→pgcopydb"
16:43:26 73794 INFO Listing COPY partitions for table "public"."rental" in "postgres://@:/pagila?"
16:43:26 73794 INFO Table "public"."rental" COPY will be split 5-ways
Part | Min | Max | Count 1/5 | 2/5 | 3211 | 3211 1 | 3212 6422 | 3211 3/5 | 6423 | 9633 | 3211 4/5 | 9634 12844 3211 5/5 | 12845 | 16049 | 3205

Listing the indexes:

<pre>\$ pgcopydb list indexes 14:35:07 13668 INF0 Listing indexes in "port 14:35:07 13668 INF0 Fetching all indexes in 14:35:07 13668 INF0 Fetched information for 0ID Schema Index Name</pre>	=54311 host=localhos source database 12 indexes conname	st dbname=pgloader" Constraint	DDL
$17002 \mid csy \mid blocks in 4r idy$	++-		+
\rightarrow csv.blocks USING gist (iprange)	1 1		CREATE INDEX DIOCKS_IP41_IUX ON
17415 csv partial b idx	1		CREATE INDEX partial b idx ON csv.
→partial USING btree (b)			· ······ ··· ··· ··· ····
17414 csv partial_a_key	partial_a_key	UNIQUE (a)	CREATE UNIQUE INDEX partial_a_key_
→ON csv.partial USING btree (a)			
17092 csv track_pkey	track_pkey	PRIMARY KEY (trackid)	CREATE UNIQUE INDEX track_pkey ON
\hookrightarrow csv.track USING btree (trackid)			
17329 err errors_pkey	errors_pkey	PRIMARY KEY (a)	CREATE UNIQUE INDEX errors_pkey
\hookrightarrow ON err.errors USING btree (a)			
16394 public allcols_pkey	allcols_pkey	PRIMARY KEY (a)	CREATE UNIQUE INDEX allcols_pkey
\hookrightarrow ON public.allcols USING btree (a)			
17054 public csv_escape_mode_pkey	<pre> csv_escape_mode_pl</pre>	key PRIMARY KEY	(id) CREATE UNIQUE INDEX csv_
⇔escape_mode_pkey ON public.csv_escape_mode	USING btree (1d)		CREATE INTONE INFER 11:0.1
1/199 public nullit_pkey	nullif_pkey	PRIMARY KEY (1d)	CREATE UNIQUE INDEX nullif_prey_
↔ ON public. nullir USING btree (1d)	l comial miror l	DDIMADY VEV (a)	CREATE UNIQUE INDEX comial phone
17455 public Serial_pkey	Serial_pkey	PRIMARI KEI (a)	CREATE UNIQUE INDEX SETTAL_PREY
\rightarrow 0N public. Serial USING Drive (a) 17288 public track full pkey	track full nkey	PRIMARY KEY (trackid)	CREATE UNIQUE INDEX track full
\rightarrow nkey ON nublic track full USING htree (track	<pre>ckid)</pre>	TRIBRIT KET (CTACKTU)	CREATE UNIQUE INDEX CLACK_IUII_
17452 public udc pkey	udc nkev	PRIMARY KEY (b)	CREATE UNIQUE INDEX udc pkey ON.
→public.udc USING btree (b)	, inception (,
17469 public xzero_pkey	xzero_pkey	PRIMARY KEY (a)	CREATE UNIQUE INDEX xzero_pkey ON_
			(continues on next page)

→public.xzero USING btree (a)

Listing the schema in JSON:

1

2

3

4 5

6

7

8 9

10 11

12

13 14 15

21

22

23

24

25

26

27 28

29 30

31

32 33

34 35

36

37

38

39

40

41 42

43

44

45

46

47

48

49 50

55 56

57

58

59 60

61 62

63

64

65 66

67 68

```
$ pgcopydb list schema --split-at 200kB
```

This gives the following JSON output:

```
{
     "setup": {
          "snapshot": "00000003-00051AAE-1",
          "source_pguri": "postgres:\/\/@:\/pagila?",
"target_pguri": "postgres:\/\/@:\/plop?",
          "table-jobs": 4,
          "index-jobs": 4,
          "split-tables-larger-than": 204800
     },
     "tables": [
          {
                "oid": 317934,
               "schema": "public",
"name": "rental",
               "reltuples": 16044,
               "bytes_pretty": "1224 kB",
"exclude-data": false,
"restore-list-name": "public rental postgres",
               "part-key": "rental_id",
                "parts": [
                     {
                          "number": 1,
                          "total": 7,
                          "min": 1,
                          "max": 2294,
                          "count": 2294
                     },
                     {
                          "number": 2,
                          "total": 7,
                          "min": 2295,
"max": 4588,
                          "count": 2294
                     },
                     {
                          "number": 3,
                          "total": 7,
                          "min": 4589,
                          "max": 6882,
                          "count": 2294
                     },
                     {
                          "number": 4,
                          "total": 7,
                          "min": 6883,
                          "max": 9176,
                          "count": 2294
                    },
{
                          "number": 5,
"total": 7,
"min": 9177,
"max": 11470,
                          "count": 2294
                     },
                     {
                          "number": 6,
                          "total": 7,
"min": 11471,
                          "max": 13764,
                          "count": 2294
                     },
                     {
                          "number": 7,
                          "total": 7,
                          "min": 13765,
"max": 16049,
```

69

70

71 72

73

74

75 76

77 78

83 84

85

86

87 88 89

90

91

92 93

94

95 96

97

98

99

100

101

102

103 104

105

106

107

108

109 110

111

112

113

114 115

116

117 118

119

120 121

126 127

128

129

130

131 132 133

139

140

141

142 143 144

145

146

(continued from previous page)

```
"count": 2285
           }
     ]
},
{
      "oid": 317818,
     "schema": "public",
"name": "film",
      "reltuples": 1000,
      "bytes": 483328,
     bytes : 405320,
"bytes-pretty": "472 kB",
"exclude-data": false,
"restore-list-name": "public film postgres",
"part-key": "film_id",
      "parts": [
           {
                  "number": 1,
                  "total": 3,
                 "min": 1,
"max": 334,
                  "count": 334
           },
           {
                  "number": 2,
                 "total": 3,
                 "min": 335,
                  "max": 668,
                  "count": 334
           },
           ł
                 "number": 3,
                  "total": 3,
                 "min": 669,
                  "max": 1000,
                  "count": 332
           }
     ]
},
{
      "oid": 317920,
     "schema": "public",
"name": "payment_p2020_04",
      "reltuples": 6754,
      "bytes": 434176,
      "bytes-pretty": "424 kB",
      "exclude-data": false,
"restore-list-name": "public payment_p2020_04 postgres",
      "part-key":
},
{
      "oid": 317916,
      "schema": "public",
"name": "payment_p2020_03",
     "name": payment_plate_of
"reltuples": 5644,
"bytes": 368640,
"bytes-pretty": "360 kB",
"exclude-data": false,
      "restore-list-name": "public payment_p2020_03 postgres",
      "part-key":
},
ł
     "oid": 317830,
     "schema": "public",
"name": "film_actor",
      "reltuples": 5462,
     "bytes_pretty": "264 kB",
"exclude-data": false,
"restore-list-name": "public film_actor postgres",
      "part-key": "
},
{
      "oid": 317885,
      "schema": "public",
"name": "inventory",
      "reltuples": 4581,
      "bytes": 270336,
      "bytes-pretty": "264 kB",
```

"exclude-data": false,
"restore-list-name": "public inventory postgres", "part-key": "inventory_id", "parts": [{ "number": 1, "total": 2, "min": 1, "max": 2291, "count": 2291 }, { "number": 2, "total": 2, "min": 2292, "max": 4581, "count": 2290 }] }, { "oid": 317912, "schema": "public", "name": "payment_p2020_02", "reltuples": 2312, "bytes": 163840, "bytes-pretty": "160 kB", "exclude-data": false, "restore-list-name": "public payment_p2020_02 postgres", "part-key": "" }, { "oid": 317784, "schema": "public", "name": "customer", "reltuples": 599, "bytes": 106496, "bytes-pretty": "104 kB", "exclude-data": false, "restore-list-name": "public customer postgres", "part-key": "customer_id" }, ł "oid": 317845, "schema": "public", "name": "address", "reltuples": 603, "bytes": 98304, "bytes-pretty": "96 kB", "exclude-data": false,
"restore-list-name": "public address postgres", "part-key": "address_id" }. { "oid": 317908, "schema": "public", "name": "payment_p2020_01", "reltuples": 1157, "bytes": 98304, "bytes . 50504, "bytes-pretty": "96 kB", "exclude-data": false, "restore-list-name": "public payment_p2020_01 postgres", "part-key": }, { "oid": 317855, "schema": "public", "name": "city", "reltuples": 600, "bytes": 73728, "bytes-pretty": "72 kB", "exclude-data": false, "restore-list-name": "public city postgres", "part-key": "city_id" }, { "oid": 317834, "schema": "public",

	"name": "film_category", "reltuples": 1000, "butes": 72728
	bytes - pretty": "72 kB", "exclude-data": false.
	<pre>"restore-list-name": "public film_category postgres", "part-key": ""</pre>
}, {	
	"oid": 317798, "schema": "public",
	"name": "actor", "reltuples": 200.
	"bytes": 49152,
	"exclude-data": false,
	<pre>"restore-list-name": "public actor postgres", "part-key": "actor_id"</pre>
}, {	
	"oid": 317924, "schema": "public",
	<pre>"name": "payment_p2020_05", "reltunles": 182.</pre>
	"bytes": 40960,
	"exclude-data": false,
	<pre>"restore-list-name": "public payment_p2020_05 postgres", "part-key": ""</pre>
}, {	
	"oid": 317808, "schema": "public",
	<pre>"name": "category", "reltuples": 0.</pre>
	"bytes": 16384,
	"exclude-data": false,
	<pre>"restore-list-name": "public category postgres", "part-key": "category_id"</pre>
}, {	
	"oid": 317865, "schema": "public".
	"name": "country", "relignes": 109
	"bytes": 16384,
	"exclude-data": false,
	<pre>"restore-list-name": "public country postgres", "part-key": "country_id"</pre>
}, {	
	"oid": 317946, "schema": "public",
	<pre>"name": "staff", "reltuples": 0,</pre>
	"bytes": 16384,
	"exclude-data": false,
	<pre>"restore-list-name:: "public staff postgres", "part-key": "staff_id"</pre>
}, {	
	"oid": 378280, "schema": "pgcopydb",
	"name": "sentinel", "reltumlee": 1
	"bytes": 8192,
	<pre>"bytes-pretty": "8192 bytes", "exclude-data": false,</pre>
	<pre>"restore-list-name": "pgcopydb sentinel dim", "part-key": ""</pre>
}, {	
-	"oid": 317892, "schema": "public".
	"name": "language",



381

382 383

384

385

386 387

388

389 390

391 392

393 394

395 396 397

398

399 400 401

402 403

404

405

406 407 408

409

410

411

412

413

414

415 416 417

418

419

420

421 422

423

424 425

426 427

428 429

430 431 432

433

434 435 436

437 438

439

440

441 442

443

444 445

446 447

448

449

450 451 452

453

458

(continued from previous page)

```
"sql": "PRIMARY KEY (actor_id)"
     }
},
{
      "oid": 317974,
     "schema": "public",
"name": "address_pkey",
      "isPrimary": true,
     "isUnique": true,
"columns": "address_id",
     "sql": "CREATE UNIQUE INDEX address_pkey ON public.address USING btree (address_id)",
"restore-list-name": "",
     "table": {
    "oid": 317845,

           "schema": "public",
"name": "address"
     },
      "constraint": {
           "oid": 317975,
"name": "address_pkey",
"sql": "PRIMARY KEY (address_id)"
     }
},
{
     "oid": 318003,
     "schema": "public",
"name": "idx_fk_city_id",
     "isPrimary": false,
     "isUnique": false,
      "columns": "city_id"
      "sql": "CREATE INDEX idx_fk_city_id ON public.address USING btree (city_id)",
      "restore-list-name": "public idx_fk_city_id postgres",
     "table": {
           "oid": 317845,
           "schema": "public",
"name": "address"
     }
}.
ł
     "oid": 317976,
     "schema": "public",
"name": "category_pkey",
      "isPrimary": true,
     "isUnique": true,
"columns": "category_id",
      "sql": "CREATE UNIQUE INDEX category_pkey ON public.category USING btree (category_id)",
"restore-list-name": "",
      "table": {
    "oid": 317808,
           "schema": "public",
"name": "category"
     3.
      "constraint": {
           "oid": 317977,
"name": "category_pkey",
"sql": "PRIMARY KEY (category_id)"
     }
},
{
     "oid": 317978,
     "schema": "public",
"name": "city_pkey"
      "isPrimary": true,
     "isUnique": true,
"columns": "city_id",
     "sql": "CREATE UNIQUE INDEX city_pkey ON public.city USING btree (city_id)",
      "restore-list-name": "
      "table": {
           "oid": 317855,
           "schema": "public",
"name": "city"
     },
      "constraint": {
           "oid": 317979,
"name": "city_pkey",
"sql": "PRIMARY KEY (city_id)"
     }
},
```





(continues on next page)

```
"schema": "public",
"name": "film"
     }
      "constraint": {
          "oid": 317989,
"name": "film_pkey",
          "sql": "PRIMARY KEY (film_id)"
     }
},
{
     "oid": 318008,
     "schema": "public",
"name": "idx_fk_language_id",
     "isPrimary": false,
     "isUnique": false,
"columns": "language_id",
     "sql": "CREATE INDEX idx_fk_language_id ON public.film USING btree (language_id)",
     "restore-list-name": "public idx_fk_language_id postgres",
     "table": {
    "oid": 317818;
          "schema": "public",
"name": "film"
     }
},
{
     "oid": 317984,
     "schema": "public",
"name": "film_actor_pkey",
     "isPrimary": true,
     "isUnique": true,
     "columns": "actor_id,film_id",
      "sql": "CREATE UNIQUE INDEX film_actor_pkey ON public.film_actor USING btree (actor_id, film_id)",
     "restore-list-name": "",
      "table": {
          "oid": 317830,
          "schema": "public",
"name": "film_actor"
     }.
      "constraint": {
          "oid": 317985,
"name": "film_actor_pkey",
          "sql": "PRIMARY KEY (actor_id, film_id)"
    }
},
ł
     "oid": 318006.
     "schema": "public",
"name": "idx_fk_film_id",
     "isPrimary": false,
     "isUnique": false,
"columns": "film_id",
     "sql": "CREATE INDEX idx_fk_film_id ON public.film_actor USING btree (film_id)",
"restore-list-name": "public idx_fk_film_id postgres",
     "table": {
          "oid": 317830,
          "schema": "public",
"name": "film_actor"
     }
},
{
     "oid": 317986.
     "schema": "public",
"name": "film_category_pkey",
     "isUnique": true,
     "columns": "film_id,category_id",
     "sql": "CREATE UNIQUE INDEX film_category_pkey ON public.film_category USING btree (film_id, category_id)",
"restore-list-name": "",
      "table": {
           "oid": 317834,
          "schema": "public",
"name": "film_category"
     }
      "constraint": {
          "oid": 317987,
"name": "film_category_pkey",
          "sql": "PRIMARY KEY (film_id, category_id)"
     }
```

(continues on next page)

615 616 617

618

619 620

621 622

623

624

625

626 627

628

629 630 631

632

633 634

635 636

637 638

639

640

641 642 643

644

645

646

647

648

649

650 651 652

653

654 655

656

657 658

659

660

661 662

663

664 665

666 667

668

669

670 671 672

673

674

675

676 677

678 679

680

681 682 683

684

685 686 687

688

689 690 691

692





(continues on next page)

849

850

851 852

853

854

855

856 857 858

859 860 861

862

863

864

865 866 867

868

869

870

871

872

873

874

875 876

877

878

879

880 881

882 883

884

885

886 887

888

889

890

891

892

893

894

895 896

897 898

899

900

901 902

903 904 905

906 907

908

909

910 911 912

913

914

915

916 917

922

923

924

925 926

```
"oid": 317916.
          "schema": "public",
          "name": "payment_p2020_03"
    }
},
ł
     "oid": 318031,
     "schema": "public",
"name": "payment_p2020_03_customer_id_idx",
     "isPrimary": false,
     "isUnique": false,
"columns": "customer_id",
     "sql": "CREATE INDEX payment_p2020_03_customer_id_idx ON public.payment_p2020_03 USING btree (customer_id)",
     "restore-list-name": "public payment_p2020_03_customer_id_idx postgres",
     "table": {
          "oid": 317916,
         "schema": "public",
"name": "payment_p2020_03"
    }
},
ł
     "oid": 318015,
     "schema": "public",
     "name": "idx_fk_payment_p2020_03_customer_id",
     "isPrimary": false,
     "isUnique": false,
     "columns": "customer_id",
     "sql": "CREATE INDEX idx_fk_payment_p2020_03_customer_id ON public.payment_p2020_03 USING btree (customer_id)",
     "restore-list-name": "public idx_fk_payment_p2020_03_customer_id postgres",
     "table": {
         "oid": 317916,
         "schema": "public",
"name": "payment_p2020_03"
    }
}.
ł
     "oid": 318032,
     "schema": "public",
"name": "payment_p2020_04_customer_id_idx",
     "isPrimary": false,
     "isUnique": false,
     "columns": "customer_id",
     "sql": "CREATE INDEX payment_p2020_04_customer_id_idx ON public.payment_p2020_04 USING btree (customer_id)",
     "restore-list-name": "public payment_p2020_04_customer_id_idx postgres",
     "table": {
          "oid": 317920.
         "schema": "public",
"name": "payment_p2020_04"
    }
},
{
     "oid": 318018,
     "schema": "public",
"name": "idx_fk_payment_p2020_04_staff_id",
     "isPrimary": false,
"isUnique": false,
"columns": "staff_id",
     "sql": "CREATE INDEX idx_fk_payment_p2020_04_staff_id ON public.payment_p2020_04 USING btree (staff_id)",
     "restore-list-name": "public idx_fk_payment_p2020_04_staff_id postgres",
     "table": {
         "oid": 317920,
         "schema": "public",
"name": "payment_p2020_04"
    }
},
{
     "oid": 318017,
     "schema": "public",
"name": "idx_fk_payment_p2020_04_customer_id",
     "isPrimary": false,
"isUnique": false,
"columns": "customer_id",
     "sql": "CREATE INDEX idx_fk_payment_p2020_04_customer_id ON public.payment_p2020_04 USING btree (customer_id)",
     "restore-list-name": "public idx_fk_payment_p2020_04_customer_id postgres",
     "table": {
          "oid": 317920,
         "schema": "public",
"name": "payment_p2020_04"
```

927 } 928 }. 929 { "oid": 318019. 930 "schema": "public",
"name": "idx_fk_payment_p2020_05_customer_id", 931 932 "isDrimary": false, "isUnique": false, "columns": "customer_id", 933 934 935 936 "sql": "CREATE INDEX idx_fk_payment_p2020_05_customer_id ON public.payment_p2020_05 USING btree (customer_id)", 937 "restore-list-name": "public idx_fk_payment_p2020_05_customer_id postgres", 938 "table": { "oid": 317924, 939 "schema": "public", "name": "payment_p2020_05" 940 941 942 } 943 }, 944 { 945 "oid": 318020, "schema": "public",
"name": "idx_fk_payment_p2020_05_staff_id", 946 947 "isPrimary": false, 948 "isUnique": false, "columns": "staff_id" "sql": "CREATE INDEX idx_fk_payment_p2020_05_staff_id ON public.payment_p2020_05 USING btree (staff_id)", "restore-list-name": "public idx_fk_payment_p2020_05_staff_id postgres", 952 "table": { "oid": 317924, "schema": "public", "name": "payment_p2020_05" 956 } }. 959 ł "oid": 318033, 960 "schema": "public", "name": "payment_p2020_05_customer_id_idx", "isPrimary": false, "isUnique": false, "columns": "customer_id", "sql": "CREATE INDEX payment_p2020_05_customer_id_idx ON public.payment_p2020_05 USING btree (customer_id)", "restore-list-name": "public payment_p2020_05_customer_id_idx postgres", 966 "table": { 968 "oid": 317924, 969 "schema": "public", "name": "payment_p2020_05" 970 971 } 972 973 }, 974 ł "oid": 318022, 975 "schema": "public",
"name": "idx_fk_payment_p2020_06_staff_id", 976 977 "isDrimary": false, "isUnique": false, "columns": "staff_id", 978 979 980 "sql": "CREATE INDEX idx_fk_payment_p2020_06_staff_id ON public.payment_p2020_06 USING btree (staff_id)", 981 "restore-list-name": "public idx_fk_payment_p2020_06_staff_id postgres", 982 "table": { 983 "oid": 317928, 984 "schema": "public", "name": "payment_p2020_06" 985 986 } 987 }, 989 { "oid": 318034, 990 "schema": "public", "name": "payment_p2020_06_customer_id_idx", 992 993 "isPrimary": false, "isUnique": false, 995 "columns": "customer_id", "sql": "CREATE INDEX payment_p2020_06_customer_id_idx ON public.payment_p2020_06 USING btree (customer_id)", 997 "restore-list-name": "public payment_p2020_06_customer_id_idx postgres", "table": { "oid": 317928, "schema": "public",
"name": "payment_p2020_06" } }, {

(continues on next page)

949

950

951

953 954

955

957

958

961

962 963

964 965

967

988

991

994

996

998 999

1000 1001 1002

1003

1004

1005

1021

1023

1027

1033

1034

1035

1062

1071

1077

1078

1079

1080 1081

```
"oid": 318021.
                       "schema": "public",
"name": "idx_fk_payment_p2020_06_customer_id",
1006
1007
                       "isPrimary": false,
1008
                       "isUnique": false,
"columns": "customer_id",
1009
1010
                       "sql": "CREATE INDEX idx_fk_payment_p2020_06_customer_id ON public.payment_p2020_06 USING btree (customer_id)",
1011
1012
                       "restore-list-name": "public idx_fk_payment_p2020_06_customer_id postgres",
                       "table": {
1013
                            "oid": 317928,
1014
                            "schema": "public",
"name": "payment_p2020_06"
1015
1016
1017
                      }
1018
                 },
1019
                 {
                       "oid": 318028,
1020
                       "schema": "public",
"name": "idx_unq_rental_rental_date_inventory_id_customer_id",
1022
                      "isPrimary": false,
"isUnique": true,
"columns": "rental_date,inventory_id,customer_id",
1024
1025
                       "sql": "CREATE UNIQUE INDEX idx_unq_rental_rental_date_inventory_id_customer_id ON public.rental USING btree_
1026
        "restore-list-name": "public idx_unq_rental_rental_date_inventory_id_customer_id postgres",
                       "table": {
1028
                            "oid": 317934,
1029
                            "schema": "public",
"name": "rental"
1030
1031
1032
                      }
                 }.
                 {
                       "oid": 317994,
                       "schema": "public",
"name": "rental_pkey",
1036
1037
                       "isPrimary": true,
1038
                       "isUnique": true,
"columns": "rental_id",
1039
1040
                       "sql": "CREATE UNIQUE INDEX rental_pkey ON public.rental USING btree (rental_id)",
"restore-list-name": "",
1041
1042
                       "table": {
1043
                            "oid": 317934,
1044
                            "schema": "public",
"name": "rental"
1045
1046
1047
                       3.
                        'constraint": {
1048
                            "oid": 317995,
"name": "rental_pkey",
1049
1050
                            "sql": "PRIMARY KEY (rental_id)"
1051
                      }
1052
1053
                 },
1054
                 {
                       "oid": 318007,
1055
                       "schema": "public",
"name": "idx_fk_inventory_id",
1056
1057
                       "isPrimary": false,
"isUnique": false,
"columns": "inventory_id",
1058
1059
1060
                       "sql": "CREATE INDEX idx_fk_inventory_id ON public.rental USING btree (inventory_id)",
1061
                       "restore-list-name": "public idx_fk_inventory_id postgres",
                       "table": {
1063
                            "oid": 317934,
1064
                            "schema": "public",
"name": "rental"
1065
1066
1067
                      }
1068
                 },
1069
                 {
                       "oid": 317996,
1070
                       "schema": "public",
"name": "staff_pkey",
1072
1073
                       "isPrimary": true,
                      "isUnique": true,
"columns": "staff_id",
1074
1075
1076
                       "sql": "CREATE UNIQUE INDEX staff_pkey ON public.staff USING btree (staff_id)",
                       "restore-list-name": "",
                       "table": {
                            "oid": 317946,
                            "schema": "public",
"name": "staff"
```
```
1082
                       },
                       "constraint": {
1083
                            "oid": 317997,
"name": "staff_pkey",
"sql": "PRIMARY KEY (staff_id)"
1084
1085
1086
                      }
1087
1088
                 },
1089
                 {
                       "oid": 318027,
1090
                       "schema": "public",
"name": "idx_unq_manager_staff_id",
1091
1092
1093
                       "isPrimary": false,
                      "isUnique": true,
"columns": "manager_staff_id",
1094
1095
1096
                       "sql": "CREATE UNIQUE INDEX idx_unq_manager_staff_id ON public.store USING btree (manager_staff_id)",
1097
                       "restore-list-name": "public idx_unq_manager_staff_id postgres",
1098
                       "table": {
1099
                            "oid": 317957,
                            "schema": "public",
"name": "store"
1100
1101
1102
                      }
1103
                 },
1104
                 {
1105
                       "oid": 317998,
1106
                       "schema": "public",
                       "name": "store_pkey",
1107
                       "isPrimary": true,
1108
1109
                       "isUnique": true,
1110
                       "columns": "store_id",
                       "sql": "CREATE UNIQUE INDEX store_pkey ON public.store USING btree (store_id)",
"restore-list-name": "",
1111
1112
                       "table": {
1113
                            "oid": 317957,
1114
                            "schema": "public",
"name": "store"
1115
1116
1117
                       },
                        'constraint": {
1118
                            "oid": 317999,
"name": "store_pkey",
1119
1120
                            "sql": "PRIMARY KEY (store_id)"
1121
                      }
1122
                 }
1123
1124
            ],
              'sequences": [
1125
1126
                 {
                       "oid": 317796,
1127
                       "schema": "public",
"name": "actor_actor_id_seq",
1128
1129
                       "last-value": 200,
1130
                       "is-called": true,
1131
                       "restore-list-name": "public actor_actor_id_seq postgres"
1132
1133
                 },
                 {
1134
                      "oid": 317843,
"schema": "public",
"name": "address_address_id_seq",
1135
1136
1137
                       "last-value": 605,
1138
                       "is-called": true,
1139
                       "restore-list-name": "public address_address_id_seq postgres"
1140
1141
                 },
1142
                 {
                       "oid": 317806,
1143
                       "schema": "public",
"name": "category_category_id_seq",
1144
1145
                       "last-value": 16,
1146
1147
                       "is-called": true,
                       "restore-list-name": "public category_category_id_seq postgres"
1148
1149
                 },
1150
                 {
1151
                       "oid": 317853,
                       "schema": "public",
"name": "city_city_id_seq",
1152
1153
1154
                       "last-value": 600,
1155
                       "is-called": true,
                       "restore-list-name": "public city_city_id_seq postgres"
1156
1157
                 },
1158
                 {
                       "oid": 317863,
1159
                                                                                                                                              (continues on next page)
```



Listing current progress (log lines removed):

(continues on next page)

		+	+
m 1 1	21		
Tables	21	4	/
Indexes	48	14	7
Indexes	48	14	/

Listing current progress, in JSON:

```
$ pgcopydb list progress --json 2>/dev/null
{
      "table-jobs": 4,
      "index-jobs": 4,
      "tables": {
            "total": 21,
            "done": 9,
            "in-progress": [
                  {
                         "oid": 317908,
                        "schema": "public",
"name": "payment_p2020_01",
                         "reltuples": 1157,
                         "bytes": 98304,
                        "bytes-pretty": "96 kB",
"exclude-data": false,
                         "restore-list-name": "public payment_p2020_01 postgres",
                         "part-key": "",
                         "process": {
"pid": 75159,
                              "start-time-epoch": 1662476249,
"start-time-string": "2022-09-06 16:57:29 CEST",
"command": "COPY \"public\".\"payment_p2020_01\""
                        }
                 },
{
                         "oid": 317855.
                        "schema": "public",
"name": "city",
"reltuples": 600,
                         "bytes": 73728,
                        "bytes": 73728,
"bytes-pretty": "72 kB",
"exclude-data": false,
"restore-list-name": "public city postgres",
"part-key": "city_id",
"process": {
    "pid": 75157,
    "start-time-epoch": 1662476249,
    "start-time-epoch": 1662476249,
    "start-time-string": "2022-09-06 16:57:29 CEST",
    "command": "COPY \"public\" \"city\""
                               "command": "COPY \"public\".\"city\"'
                        }
                 }
           ]
      },
          "indexes": {
            "total": 48,
            "done": 39,
            "in-progress": [
                  {
                         "oid": 378283,
                        "schema": "pgcopydb",
"name": "sentinel_expr_idx",
                         "isPrimary": false,
                        "isUnique": true,
"columns": "",
                         "sql": "CREATE UNIQUE INDEX sentinel_expr_idx ON pgcopydb.sentinel USING btree ((1))",
                         "restore-list-name": "pgcopydb sentinel_expr_idx dim",
                         "table": {
                               "oid": 378280,
                              "schema": "pgcopydb",
"name": "sentinel"
                        },
                         "process": {
                              "pid": 74372,
"start-time-epoch": 1662476080,
                               "start-time-string": "2022-09-06 16:54:40 CEST"
                        }
                  },
                  {
                         "oid": 317980,
                        "schema": "public",
```

(continues on next page)

```
(continued from previous page)
```

```
"name": "country_pkey",
                    "isPrimary": true,
                    "isUnique": true,
"columns": "country_id",
                    "sql": "CREATE UNIQUE INDEX country_pkey ON public.country USING btree (country_id)",
                    "restore-list-name": "public country_pkey postgres",
                    "table": {
    "oid": 317865,
                         "schema": "public",
"name": "country"
                   "oid": 317981,
"name": "country_pkey",
"sql": "PRIMARY KEY (country_id)",
                         "restore-list-name":
                    },
                    "process": {
                         "pid": 74358,
                         "start-time-epoch": 1662476080,
                         "start-time-string": "2022-09-06 16:54:40 CEST"
                    }
              },
               {
                    "oid": 317996,
                    "schema": "public",
"name": "staff_pkey",
                    "isPrimary": true,
                    "isUnique": true,
                    "columns": "staff_id"
                    "sql": "CREATE UNIQUE INDEX staff_pkey ON public.staff USING btree (staff_id)",
                    "restore-list-name": "public staff_pkey postgres",
                    "table": {
                         "oid": 317946,
                         "schema": "public",
"name": "staff"
                    }.
                     'constraint": {
                         "oid": 317997,
                         "name": "staff_pkey",
"sql": "PRIMARY KEY (staff_id)",
                         "restore-list-name":
                   },
"process": {
    "pid": 74368,
    "**-time-e"
                         "start-time-epoch": 1662476080,
"start-time-string": "2022-09-06 16:54:40 CEST"
                   3
              }
         ]
    }
}
```

4.9 pgcopydb stream

pgcopydb stream - Stream changes from source database

Warning: This mode of operations has been designed for unit testing only.

Consider using the pgcopydb clone (with the --follow option) or the pgcopydb follow command instead.

Note: Some pgcopydb stream commands are still designed for normal operations, rather than unit testing only.

The pgcopydb stream sentinel set startpos, pgcopydb stream sentinel set endpos, pgcopydb stream sentinel set apply, and pgcopydb stream sentinel set prefetch commands are necessary to communicate with the main pgcopydb clone --follow or pgcopydb follow process. See Change Data Capture Example 1 for a detailed example using pgcopydb stream sentinel set endpos.

Also the commands *pgcopydb stream setup* and *pgcopydb stream cleanup* might be used directly in normal operations. See *Change Data Capture Example 2* for a detailed example.

This command prefixes the following sub-commands:

pgcopydb str	eam				
setup	Setup source and target systems for logical decoding				
cleanup	cleanup source and target systems for logical decoding				
prefetch	Stream JSON changes from the source database and transform them to SQL				
catchup	Apply prefetched changes from SQL files to the target database				
+ create	Create resources needed for pgcopydb				
+ drop	Drop resources needed for pgcopydb				
+ sentinel	Maintain a sentinel table on the source database				
receive	Stream changes from the source database				
transform	Transform changes from the source database into SQL commands				
apply	Apply changes from the source database into the target database				
naconvdh str	pam create				
slot Cr	and a replication slot in the source database				
origin Cr	rate a replication origin in the target database				
J J					
pgcopydb str	eam drop				
slot Dr	op a replication slot in the source database				
origin Dr	n Drop a replication origin in the target database				
pgcopydb str	am sentinel				
dron Dr	ate the senting table on the source database				
ant Co	by the sentinel table on the source database				
yet de	Get the sentinel table values on the source database				
1 300 114	intent a sentinci cable on the source alcabase				
pgcopydb str	eam sentinel set				
startpos	Set the sentinel start position LSN on the source database				
endpos	Set the sentinel end position LSN on the source database				
apply	Set the sentinel apply mode on the source database				
prefetch	Set the sentinel prefetch mode on the source database				

Those commands implement a part of the whole database replay operation as detailed in section *pgcopydb follow*. Only use those commands to debug a specific part, or because you know that you just want to implement that step.

Note: The sub-commands stream setup then stream prefetch and stream catchup are higher level commands, that use internal information to know which files to process. Those commands also keep track of their progress.

The sub-commands stream receive, stream transform, and stream apply are lower level interface that work on given files. Those commands still keep track of their progress, but have to be given more information to work.

4.9.1 pgcopydb stream setup

pgcopydb stream setup - Setup source and target systems for logical decoding

The command pgcopydb stream setup connects to the source database and creates a replication slot using the logical decoding plugin wal2json, then creates a pgcopydb.sentinel table, and then connects to the target database and creates a replication origin positioned at the LSN position of the just created replication slot.

```
pgcopydb stream setup: Setup source and target systems for logical decoding
usage: pgcopydb stream setup
                              --source ... --target ... --dir
                   Postgres URI to the source database
  --source
                   Postgres URI to the target database
  --target
  --dir
                   Work directory to use
                   Allow restarting when temp files exist already
  --restart
  --resume
                   Allow resuming operations after a failure
  --not-consistent Allow taking a new snapshot on the source database
  --snapshot
                   Use snapshot obtained with pg_export_snapshot
  --slot-name
                   Stream changes recorded by this slot
  --origin
                   Name of the Postgres replication origin
```

4.9.2 pgcopydb stream cleanup

pgcopydb stream cleanup - cleanup source and target systems for logical decoding

The command pgcopydb stream cleanup connects to the source and target databases to delete the objects created in the pgcopydb stream setup step.

```
pgcopydb stream cleanup: cleanup source and target systems for logical decoding
usage: pgcopydb stream cleanup
                                --source ... --target ... --dir ..
  --source
                   Postgres URI to the source database
  --target
                   Postgres URI to the target database
  --dir
                   Work directory to use
                   Allow restarting when temp files exist already
  --restart
                   Allow resuming operations after a failure
  --resume
  --not-consistent Allow taking a new snapshot on the source database
  --snapshot
                   Use snapshot obtained with pg_export_snapshot
                   Stream changes recorded by this slot
  --slot-name
  --origin
                   Name of the Postgres replication origin
```

4.9.3 pgcopydb stream prefetch

pgcopydb stream prefetch - Stream JSON changes from the source database and transform them to SQL

The command pgcopydb stream prefetch connects to the source database using the logical replication protocl and the given replication slot, that should be created with the logical decoding plugin wal2json.

The prefetch command receives the changes from the source database in a streaming fashion, and writes them in a series of JSON files named the same as their origin WAL filename (with the .json extension). Each time a JSON file is closed, a subprocess is started to transform the JSON into an SQL file.

```
pgcopydb stream prefetch: Stream JSON changes from the source database and transform them to SQL
usage: pgcopydb stream prefetch
                                 --source ...
  --source
                   Postgres URI to the source database
 --dir
                   Work directory to use
                   Allow restarting when temp files exist already
  --restart
  --resume
                   Allow resuming operations after a failure
  --not-consistent Allow taking a new snapshot on the source database
                   Stream changes recorded by this slot
  --slot-name
                   LSN position where to stop receiving changes
  --endpos
```

4.9.4 pgcopydb stream catchup

pgcopydb stream catchup - Apply prefetched changes from SQL files to the target database

The command pgcopydb stream catchup connects to the target database and applies changes from the SQL files that have been prepared with the pgcopydb stream prefetch command.

```
pgcopydb stream catchup: Apply prefetched changes from SQL files to the target database
usage: pgcopydb stream catchup
                                --source ... --target
  --source
                   Postgres URI to the source database
  --target
                   Postgres URI to the target database
 --dir
                   Work directory to use
  --restart
                   Allow restarting when temp files exist already
                   Allow resuming operations after a failure
  --resume
  --not-consistent Allow taking a new snapshot on the source database
  --slot-name
                   Stream changes recorded by this slot
                   LSN position where to stop receiving changes --origin
                                                                                   Name of the Postgres replication origin
  --endpos
```

4.9.5 pgcopydb stream create slot

pgcopydb stream create slot - Create a replication slot in the source database

The command pgcopydb stream create slot connects to the source database and executes a SQL query to create a logical replication slot using the plugin wal2json.

```
pgcopydb create slot: Create a replication slot in the source database
usage: pgcopydb create slot --source ...

--source Postgres URI to the source database
--dir Work directory to use
--snapshot Use snapshot obtained with pg_export_snapshot
--slot-name Use this Postgres replication slot name
```

4.9.6 pgcopydb stream create origin

pgcopydb stream create origin - Create a replication origin in the target database

The command pgcopydb stream create origin connects to the target database and executes a SQL query to create a logical replication origin. The starting LSN position --startpos is required.

```
pgcopydb stream create origin: Create a replication origin in the target database
usage: pgcopydb stream create origin --target ...

--target Postgres URI to the target database

--dir Work directory to use

--origin Use this Postgres origin name

--start-pos LSN position from where to start applying changes
```

4.9.7 pgcopydb stream drop slot

pgcopydb stream drop slot - Drop a replication slot in the source database

The command pgcopydb stream drop slot connects to the source database and executes a SQL query to drop the logical replication slot with the given name (that defaults to pgcopydb).

```
pgcopydb stream drop slot: Drop a replication slot in the source database
usage: pgcopydb stream drop slot --source ...

--source Postgres URI to the source database

--dir Work directory to use

--slot-name Use this Postgres replication slot name
```

4.9.8 pgcopydb stream drop origin

pgcopydb stream drop origin - Drop a replication origin in the target database

The command pgcopydb stream drop origin connects to the target database and executes a SQL query to drop the logical replication origin with the given name (that defaults to pgcopydb).

```
usage: pgcopydb stream drop origin --target ...

--target Postgres URI to the target database

--dir Work directory to use

--origin Use this Postgres origin name
```

4.9.9 pgcopydb stream sentinel create

pgcopydb stream sentinel create - Create the sentinel table on the source database

The pgcopydb.sentinel table allows to remote control the prefetch and catchup processes of the logical decoding implementation in pgcopydb.

```
pgcopydb stream sentinel create: Create the sentinel table on the source database
usage: pgcopydb stream sentinel create --source ...
--source Postgres URI to the source database
--startpos Start replaying changes when reaching this LSN
--endpos Stop replaying changes when reaching this LSN
```

4.9.10 pgcopydb stream sentinel drop

pgcopydb stream sentinel drop - Drop the sentinel table on the source database

The pgcopydb.sentinel table allows to remote control the prefetch and catchup processes of the logical decoding implementation in pgcopydb.

```
pgcopydb stream sentinel drop: Drop the sentinel table on the source database
usage: pgcopydb stream sentinel drop --source ...
--source Postgres URI to the source database
```

4.9.11 pgcopydb stream sentinel get

pgcopydb stream sentinel get - Get the sentinel table values on the source database

```
pgcopydb stream sentinel get: Get the sentinel table values on the source database
usage: pgcopydb stream sentinel get --source ...
--source Postgres URI to the source database
--json Format the output using JSON
```

4.9.12 pgcopydb stream sentinel set startpos

pgcopydb stream sentinel set startpos - Set the sentinel start position LSN on the source database

pgcopydb stream sentinel set startpos: Set the sentinel start position LSN on the source database usage: pgcopydb stream sentinel set startpos --source ... <start LSN> --source Postgres URI to the source database

4.9.13 pgcopydb stream sentinel set endpos

pgcopydb stream sentinel set endpos - Set the sentinel end position LSN on the source database

```
pgcopydb stream sentinel set endpos: Set the sentinel end position LSN on the source database
usage: pgcopydb stream sentinel set endpos --source ... <end LSN>
--source Postgres URI to the source database
--current Use pg_current_wal_flush_lsn() as the endpos
```

4.9.14 pgcopydb stream sentinel set apply

pgcopydb stream sentinel set apply - Set the sentinel apply mode on the source database

```
pgcopydb stream sentinel set apply: Set the sentinel apply mode on the source database
usage: pgcopydb stream sentinel set apply --source ... <true|false>
--source Postgres URI to the source database
```

4.9.15 pgcopydb stream sentinel set prefetch

pgcopydb stream sentinel set prefetch - Set the sentinel prefetch mode on the source database

```
pgcopydb stream sentinel set prefetch: Set the sentinel prefetch mode on the source database
usage: pgcopydb stream sentinel set prefetch --source ... <true|false>
--source Postgres URI to the source database
```

4.9.16 pgcopydb stream receive

pgcopydb stream receive - Stream changes from the source database

The command pgcopydb stream receive connects to the source database using the logical replication protocl and the given replication slot, that should be created with the logical decoding plugin wal2json.

The receive command receives the changes from the source database in a streaming fashion, and writes them in a series of JSON files named the same as their origin WAL filename (with the .json extension).

```
pgcopydb stream receive: Stream changes from the source database
usage: pgcopydb stream receive --source ...
--source Postgres URI to the source database
--dir Work directory to use
--restart Allow restarting when temp files exist already
--resume Allow resuming operations after a failure
--not-consistent Allow taking a new snapshot on the source database
--slot-name Stream changes recorded by this slot
--endpos LSN position where to stop receiving changes
```

4.9.17 pgcopydb stream transform

pgcopydb stream transform - Transform changes from the source database into SQL commands

The command pgcopydb stream transform transforms a JSON file as received by the pgcopydb stream receive command into an SQL file with one query per line.

```
pgcopydb stream transform: Transform changes from the source database into SQL commands
usage: pgcopydb stream transform [ --source ... ] <json filename> <sql filename>
--source Postgres URI to the source database
--dir Work directory to use
--restart Allow restarting when temp files exist already
--resume Allow resuming operations after a failure
--not-consistent Allow taking a new snapshot on the source database
```

4.9.18 pgcopydb stream apply

pgcopydb stream apply - Apply changes from the source database into the target database

The command pgcopydb stream apply applies a SQL file as prepared by the pgcopydb stream transform command in the target database. The apply process tracks progress thanks to the Postgres API for Replication Progress Tracking.

```
pgcopydb stream apply: Apply changes from the source database into the target database
usage: pgcopydb stream apply --target ... <sql filename>
--target Postgres URI to the target database
--dir Work directory to use
--restart Allow restarting when temp files exist already
--resume Allow resuming operations after a failure
--not-consistent Allow taking a new snapshot on the source database
--origin Name of the Postgres replication origin
```

4.9.19 Options

The following options are available to pgcopydb stream sub-commands:

source	Connection string to the source Postgres instance. See the Postgres documentation for connection strings for the details. In short both the quoted form "host= dbname=" and the URI form postgres://user@host:5432/dbname are supported.
target	Connection string to the target Postgres instance.
dir	During its normal operations pgcopydb creates a lot of temporary files to track sub-processes progress. Temporary files are created in the directory location given by this option, or defaults to \${TMPDIR}/pgcopydb when the environment variable is set, or then to /tmp/pgcopydb.
	Change Data Capture files are stored in the cdc sub-directory of thedir option when provided, otherwise see XDG_DATA_HOME environment variable below.
restart	When running the pgcopydb command again, if the work directory already con- tains information from a previous run, then the command refuses to proceed and delete information that might be used for diagnostics and forensics.
	In that case, therestart option can be used to allow pgcopydb to delete traces from a previous run.
resume	When the pgcopydb command was terminated before completion, either by an interrupt signal (such as C-c or SIGTERM) or because it crashed, it is possible to resume the database migration.
	To be able to resume a streaming operation in a consistent way, all that's required is re-using the same replication slot as in previous run(s).
slot-name	Logical replication slot to use. At the moment pgcopydb doesn't know how to create the logical replication slot itself. The slot should be created within the same transaction snapshot as the initial data copy.
	Must be using the wal2json output plugin, available with format-version 2.
endpos	Logical replication target LSN to use. Automatically stop replication and exit with normal exit status 0 when receiving reaches the specified LSN. If there's a record with LSN exactly equal to lsn, the record will be output.

	Theendpos option is not aware of transaction boundaries and may truncate output partway through a transaction. Any partially output transaction will not be consumed and will be replayed again when the slot is next read from. Individual messages are never truncated.
	See also documentation for pg_recvlogical.
origin	Logical replication target system needs to track the transactions that have been applied already, so that in case we get disconnected or need to resume operations we can skip already replayed transaction.
	Postgres uses a notion of an origin node name as documented in Replication Progress Tracking. This option allows to pick your own node name and defaults to "pgcopydb". Picking a different name is useful in some advanced scenarios like migrating several sources in the same target, where each source should have their own unique origin node name.
startpos	Logical replication target system registers progress by assigning a current LSN to theorigin node name. When creating an origin on the target database system, it is required to provide the current LSN from the source database system, in order to properly bootstrap pgcopydb logical decoding.
verbose	Increase current verbosity. The default level of verbosity is INFO. In ascending order pgcopydb knows about the following verbosity levels: FATAL, ERROR, WARN, INFO, NOTICE, DEBUG, TRACE.
debug	Set current verbosity to DEBUG level.
trace	Set current verbosity to TRACE level.
quiet	Set current verbosity to ERROR level.

4.9.20 Environment

PGCOPYDB_SOURCE_PGURI

Connection string to the source Postgres instance. When --source is ommitted from the command line, then this environment variable is used.

PGCOPYDB_TARGET_PGURI

Connection string to the target Postgres instance. When --target is ommitted from the command line, then this environment variable is used.

TMPDIR

The pgcopydb command creates all its work files and directories in ${TMPDIR}/pgcopydb$, and defaults to /tmp/pgcopydb.

XDG_DATA_HOME

The pgcopydb command creates Change Data Capture files in the standard place XDG_DATA_HOME, which defaults to ~/.local/share. See the XDG Base Directory Specification.

4.9.21 Examples

2

3 4

5

6

8

9 10

11 12

13

As an example here is the output generated from running the cdc test case, where a replication slot is created before the initial copy of the data, and then the following INSERT statement is executed:

```
begin;
with r as
(
    insert into rental(rental_date, inventory_id, customer_id, staff_id, last_update)
        select '2022-06-01', 371, 291, 1, '2022-06-01'
    returning rental_id, customer_id, staff_id
)
insert into payment(customer_id, staff_id, rental_id, amount, payment_date)
        select customer_id, staff_id, rental_id, 5.99, '2020-06-01'
        from r;
commit:
```

The command then looks like the following, where the --endpos has been extracted by calling the pg_current_wal_lsn() SQL function:

\$ pgcopydb stream receive --slot-name test_slot --restart --endpos 0/236D668 -vv 16:01:57 157 INFO Running pgcopydb version 0.7 from "/usr/local/bin/pgcopydb' 16:01:57 157 DEBUG copydb.c:406 Change Data Capture data is managed at "/var/lib/postgres/.local/share/pgcopydb" 16:01:57 157 INFO copydb.c:73 Using work dir "/tmp/pgcopydb" 16:01:57 157 DEBUG pidfile.c:143 Failed to signal pid 34: No such process 16:01:57 157 DEBUG pidfile.c:146 Found a stale pidfile at "/tmp/pgcopydb/pgcopydb.pid" 16:01:57 157 INFO pidfile.c:147 Removing the stale pid file "/tmp/pgcopydb/pgcopydb.pid" 16:01:57 157 INFO copydb.c:254 Work directory "/tmp/pgcopydb" already exists 16:01:57 157 INFO copydb.c:258 A previous run has run through completion 16:01:57 157 INFO copydb.c:151 Removing directory "/tmp/pgcopydb" 16:01:57 157 DEBUG copydb.c:445 rm -rf "/tmp/pgcopydb" && mkdir -p "/tmp/pgcopydb" 16:01:57 157 DEBUG copydb.c:445 rm -rf "/tmp/pgcopydb/schema" && mkdir -p "/tmp/pgcopydb/s 16:01:57 157 DEBUG copydb.c:445 rm -rf "/tmp/pgcopydb/run" && mkdir -p "/tmp/pgcopydb/run" "/tmp/pgcopydb/schema" 16:01:57 157 DEBUG copydb.c:445 rm -rf "/tmp/pgcopydb/run/tables" && mkdir -p "/tmp/pgcopydb/run/tables" 16:01:57 157 DEBUG copydb.c:445 rm -rf "/tmp/pgcopydb/run/indexes" && mkdir -p "/tmp/pgcopydb/run/indexes" 16:01:57 157 DEBUG copydb.c:445 rm -rf "/var/lib/postgres/.local/share/pgcopydb" && mkdir -p "/var/lib/postgres/.local/share/ →pgcopydb" 16:01:57 157 DEBUG pgsql.c:2476 starting log streaming at 0/0 (slot test_slot) 16:01:57 157 DEBUG pgsql.c:485 Connecting to [source] "postgres://postgres@source:/postgres?password=****&replication=database" 16:01:57 157 DEBUG pgsql.c:2009 IDENTIFY_SYSTEM: timeline 1, xlogpos 0/236D668, systemid 7104302452422938663 16:01:57 157 DEBUG pgsql.c:3188 RetrieveWalSegSize: 16777216 16:01:57 157 DEBUG pgsql.c:2547 streaming initiated 16:01:57 157 DEBUG stream.c:341 Received action B for XID 488 in LSN 0/236D638 16:01:57 157 DEBUG stream.c:341 Received action I for XID 488 in LSN 0/236D178 16:01:57 157 DEBUG stream.c:341 Received action I for XID 488 in LSN 0/236D308 16:01:57 157 DEBUG stream.c:341 Received action C for XID 488 in LSN 0/236D638 16:01:57 157 DEBUG pgsql.c:2867 pgsql_stream_logical: endpos reached at 0/236D668 16:01:57 157 DEBUG stream.c:382 Flushed up to 0/236D668 in file "/var/lib/postgres/.local/share/pgcopydb/ →00000001000000000000000002.json" 16:01:57 157 INFO pgsql.c:3030 Report write_lsn 0/236D668, flush_lsn 0/236D668 16:01:57 157 DEBUG pgsql.c:3107 end position 0/236D668 reached by WAL record at 0/236D668 16:01:57 157 DEBUG pgsql.c:408 Disconnecting from [source] "postgres://postgres@source:/postgres?password=****& →replication=database' →ison' 16:01:57 157 INFO stream.c:171 Streaming is now finished after processing 4 messages

The JSON file then contains the following content, from the *wal2json* logical replication plugin. Note that you're seeing different LSNs here because each run produces different ones, and the captures have not all been made from the same run.

```
(continues on next page)
```

```
→ "name":"staff_id","type":"integer","value":1},{"name":"rental_id","type":"integer","value":16050},{"name":"amount","type":
→ "numeric(5,2)","value":5.99},{"name":"payment_date","type":"timestamp with time zone","value":"2020-06-01 00:00:00+00"}]}
{"action":"C","xid":489,"timestamp":"2022-06-27 13:24:31.460822+00","lsn":"0/236F5A8","nextlsn":"0/236F5D8"}
```

It's then possible to transform the JSON into SQL:

\$ pgcopydb stream transform ./tests/cdc/000000010000000000002.json /tmp/00000001000000000002.sql

And the SQL file obtained looks like this:

4.10 pgcopydb configuration

Manual page for the configuration of pgcopydb. The pgcopydb command accepts sub-commands and command line options, see the manual for those commands for details. The only setup that pgcopydb commands accept is the filtering.

4.10.1 Filtering

Filtering allows to skip some object definitions and data when copying from the source to the target database. The pgcopydb commands that accept the option --filter (or --filters) expect an existing filename as the option argument. The given filename is read in the INI file format, but only uses sections and option keys. Option values are not used.

Here is an inclusion based filter configuration example:

```
[include-only-table]
    public.allcols
2
     public.csv
3
    public.serial
    public.xzero
5
6
    [exclude-index]
7
    public.foo_gin_tsvector
9
    [exclude-table-data]
10
    public.csv
11
```

Here is an exclusion based filter configuration example:

```
[exclude-schema]
2
     foo
3
     bar
     expected
5
     [exclude-table]
6
      schema"."name
7
     schema.othername
8
9
     err.errors
10
    public.serial
11
     [exclude-index]
12
     schema.indexname
13
14
15
     [exclude-table-data]
     public.bar
16
     nsitra.test1
17
```

Filtering can be done with pgcopydb by using the following rules, which are also the name of the sections of the INI file.

include-only-tables

This section allows listing the exclusive list of the source tables to copy to the target database. No other table will be processed by pgcopydb.

Each line in that section should be a schema-qualified table name. Postgres identifier quoting rules can be used to avoid ambiguity.

When the section include-only-tables is used in the filtering configuration then the sections exclude-schema and exclude-table are disallowed. We would not know how to handle tables that exist on the source database and are not part of any filter.

exclude-schema

This section allows adding schemas (Postgres namespaces) to the exclusion filters. All the tables that belong to any listed schema in this section are going to be ignored by the pgcopydb command.

This section is not allowed when the section include-only-tables is used.

exclude-table

This section allows to add a list of qualified table names to the exclusion filters. All the tables that are listed in the exclude-table section are going to be ignored by the pgcopydb command.

This section is not allowed when the section include-only-tables is used.

exclude-index

This section allows to add a list of qualified index names to the exclusion filters. It is then possible for pgcopydb to operate on a table and skip a single index definition that belong to a table that is still processed.

exclude-table-data

This section allows to skip copying the data from a list of qualified table names. The schema, index, constraints, etc of the table are still copied over.

4.10.2 Reviewing and Debugging the filters

Filtering a pg_restore archive file is done through rewriting the archive catalog obtained with pg_restore --list. That's a little hackish at times, and we also have to deal with dependencies in pgcopydb itself.

The following commands can be used to explore a set of filtering rules:

- pgcopydb list depends
- pgcopydb restore parse-list

CHAPTER

FIVE

INDICES AND TABLES

- genindex
- modindex
- search